



A CSW Industrials Company

PRODUCT DATA SHEET

FOAM-CORE™

High strength, max foam condenser coil cleaner

Description

Foam-Core's penetrating surfactant foaming action lifts and pushes contaminants and grease out of areas of the coil which are normally inaccessible, to where they can be rinsed away with low pressure water. Leaves aluminum surfaces clean in less than five minutes. Foam-Core's powerful foaming cleaning formula is suitable for condenser coils and can be used on electronic air filters.

READ ALL SDS, DIRECTIONS AND WARNINGS ON LABEL BEFORE USE

Directions for Use:

- Dilute FOAM-CORE with cold water only (below 100°F)
 - For brightening, oxides, heavy dirt & grease removal** - 1 part FOAM-CORE to 3 parts water.
 - For some brightening, light to medium dirt & grease removal** - 1 part FOAM-CORE to 6 parts water.
 - For no brightening, light dirt removal** - 1 part FOAM-CORE to 9 parts water.
- Shut off system.
- Spray the diluted FOAM-CORE on to all surfaces, saturating the coils well. Use a low-pressure sprayer that does not contain aluminum. Do not use high pressure washers. Avoid back spray from wind.
- Allow 5 minutes for full cleaning action, but never more than 8 minutes.
- Rinse coils and surrounding area very thoroughly with low pressure water.
- For cooking grease applications, allow the full 8 minutes before rinsing. Repeat if necessary.



Characteristics | Features

- Commercial strength
- Alkaline base
- Biodegradable*
- Maximum foaming action penetrates stubborn grease, tars and dirt, solubilizes and disperses them so they can be rinsed away with water
- Concentrated – dilute with water for economical use
- Leaves aluminum surfaces not only bright and shiny, but also completely clean and free of particulate matter in less than 5 minutes

*Contains the best available biodegradable surfactants and detergents

Packaging

Code	Size	Qty. per Case	Lbs. per Case	Cubic Feet
11050	Gallon (3.8 L)	4 Bottles	45	1.21

FOAM-CORE™

High strength, max foam condenser coil cleaner

Specifications

Wt/Gal @ 77°F	10 lbs./gal.
Flash Point	None
Color	Yellow
Shelf Life	2 years

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances

Precautionary Statements

Refer to Safety Data Sheet (SDS).

KEEP OUT OF REACH OF CHILDREN

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300

For additional Technical Information Call Toll Free 1-800-231-3345

Limited Warranty



For more information on our product limited warranty, visit RectorSeal.com

Manufactured by

RectorSeal, LLC

2601 Spenwick Drive • Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • rectorseal.com

3255 Wyandotte St. East • Windsor, ON N8Y 1E9, Canada • 519-966-4901

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2023 RectorSeal. All rights reserved. R50400-0323