



A CSW Industrials Company

PRODUCT DATA SHEET

SAM™ CL-3L

Low-VOC Cleaner for PVC, CPVC and ABS

Description

Sam CL-3L is a clear cleaner for use on all PVC, CPVC and ABS pipe, tubing, and socket-type fittings. Max VOC per SCAQMD 1171: 25 g/L.

Instructions

- 1. Store between 40°F and 110°F and apply between -15°F and 120°F. Use below 40° F only with proper solvent cement and with extreme care. Use this cleaner to remove grease, oil, and dirt from bonding surfaces of PVC, CPVC and ABS pipe and fittings. Wear non-permeable gloves during application to avoid skin contact.
2. Clean fitting socket and pipe, and check for proper fit.
3. Using supplied dauber applicator, apply CLEANER evenly and freely to socket and then to pipe end for length of socket depth. Then apply again to socket. Avoid puddling. For pipe greater than 2" diameter use natural-bristle brush sized to 1/2 of the pipe diameter.
4. Temperature and humidity conditions may require repeated applications to one or both surfaces to avoid drying. While still wet, quickly apply proper solvent cement and make up pipe joint in accordance with the solvent cement's instructions.

For additional technical information, call Toll Free 1-800-231-3345.

Applications

Sam CL-3L is specifically formulated as a cleaner for use on all PVC, CPVC, and ABS pipe applications such as potable water, pressure pipe, conduit, sewers and drain, waste and vent (DWV). It is for use with all sizes and classes in both Schedule 40 and Schedule 80.



Characteristics | Features

- Safe for use on potable water systems
• Helps make a clean, professional looking joint
• Acts as a cleaner by dissolving grease and dirt and helping prepare the bonding surfaces for solvent cementing
• Good for PVC, CPVC and ABS systems

Packaging

Table with 5 columns: Code, Size, Qty. per Case, Lbs. per Case, Cubic Ft per Case. Rows include 1/4 Pint Dauber top (118 ml), 1/2 Pint Dauber top (237 ml), Pint Dauber top (473 ml), and Quart Dauber top (946 ml).

SAM™ CL-3L

Low-VOC Cleaner for PVC, CPVC and ABS

Specifications

Wt/Gal @ 77°F	6.5 lbs./gal.
Flash Point SETA CC	-20°C (-4°F) TCC based on Acetone
Color	Clear
Shelf Life	3 years

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

Precautionary Statements

Refer to Safety Data Sheet (SDS).

KEEP OUT OF REACH OF CHILDREN

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300

For additional Technical Information Call Toll Free 1-800-231-3345

Limited Warranty



For more information on our product limited warranty, visit RectorSeal.com

Distributed by

RectorSeal, LLC

2601 Spenwick Drive • Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • rectorseal.com

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2021 RectorSeal. All rights reserved. R50099-1121