



A CSW Industrials Company

PRODUCT DATA SHEET

SURGEX™ Boiler treatment

Description

SURGEX helps to eliminate priming, surging, and foaming in steam boilers by freeing entrapped air bubbles. SURGEX contains inhibitors that prevent corrosion and hard water mineral scale.

Applications

Surgex is used to cure priming, surging and foaming in boilers and is especially effective in inhibiting scale and corrosion. It has a concentrated anti-foam formula, color-coded to ensure proper treatment.



Directions for Use

READ ALL DIRECTIONS, SDS AND LABEL BEFORE USING

(1) Completely drain boiler to flush previously installed chemicals, and refill boiler. (2) Relieve system pressure. (3) Add 1 container of Surgex per 600 sq. ft. radiation through safety valve (4) Fire boiler for 15 min. If gauge glass is not green, add more Surgex. Surgex remains in the system to inhibit surging and corrosion.

For additional technical information, call Toll Free 1-800-231-3345

Characteristics | Features

- Inhibits corrosion
- Produces clean, dry steam
- Contains no petroleum distillates
- Color coded

Packaging

Code	Size	Qty. per Case	Lbs. per Case	Cubic Ft per Case
68752	1.5 oz (42.5 g)	20	7	0.17

Specifications

Wt/Gal @ 77°F	Solid
Flash Point SETA CC	None
Color	Orange powder
Shelf Life	2 years

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.



DANGER!

May form combustible dust concentration in air. Causes serious eye damage. Harmful if inhaled. Harmful if swallowed. May cause damage to organs (respiratory system) through prolonged or repeated exposure (inhalation).

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300.

Contains: EDTA 64-02-8, Sodium sulfite 7558-80-7, Sodium carbonate 497-19-8.

Precautionary Statements: PREVENTION: Use only outdoors or in a well-ventilated area. Wear eye/face protection. Avoid breathing dust. Do not breathe dust/gas/mist/vapors. Do not eat, drink or smoke when using this product. Wash with plenty of water and soap thoroughly after handling.

RESPONSE: Immediately call a POISON CENTER or doctor/physician. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. **IF SWALLOWED:** Call a POISON CENTER/doctor if you feel unwell. Rinse mouth. **DISPOSAL:** Dispose of contents/container to an approved waste disposal plant. **KEEP OUT OF REACH OF CHILDREN.**

For additional information, refer to Safety Data Sheet, or Call Toll Free 1-800-231-3345.

Limited Warranty

RectorSeal, LLC makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RectorSeal, LLC. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal, LLC shall not be liable for incidental or consequential damages.

Manufactured by

RectorSeal, LLC

2601 Spenwick Drive • Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • rectorseal.com

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2020 RectorSeal. All rights reserved. R50490-0820