



A CSW Industrials Company

PRODUCT DATA SHEET

BREAK-OUT™ AEROSOL  
High temperature anti-seize & lubricant

Description

Break-Out Anti-Seize Lubricant is a copper graphite compound dispersed in a water resistant grease and fortified with CZ-EX (RectorSeal's patented EP additive) to provide unmatched protection. Break-Out reduces friction and prevents galling, seizing, heat freeze, rust and corrosion in metal-to-metal contact applications.

Applications

Bolts, nuts & screws, bushings, U-bolts, studs, pipe fittings, gaskets, tops & drills, flanges, unions, chains, valve stems, cylinders, heads, boilers, turbines, furnaces, engines, autoclaves, reactors & heat exchangers.

Directions for Use:

READ ALL SDS, DIRECTIONS AND WARNINGS ON LABEL BEFORE USE

1. Shake well, rattle ball for 30 seconds before spraying.
2. Clean surface thoroughly.
3. Hold can 6 inches from surface, depress spray tip and apply a thin even coat. To prevent clogging nozzle, shake vigorously and often.
4. After use, turn can upside down and spray until clear.

NOTE: Do not use on stainless steel exposed to temperatures above 550°F. Not for use on oxygen or LPG lines.

For additional technical information, call Toll Free 1-800-231-3345.



Characteristics | Features

- Reduced VOC formula Contains less than 350 grams per liter VOCs
- Protects Against Seizing
- Service Rating Up To 1800°F
- Meets military specification MIL-PRF-907F
- Will not run, drip or settle out

Packaging

Code	Size	Qty. per Case	Lbs. per Case	Cubic Feet
73861	12 oz. aerosol (341 g)	12 cans	12	0.46

# BREAK-OUT™ AEROSOL

High temperature anti-seize & lubricant

## Specifications

Wt/Gal @ 77° F	10.1 lbs/gal
Flash Point Cleveland Open Cup	>450° F
Color	Bronze
Shelf Life	2 years
Federal Specification	MIL-PRF-907F

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances



### DANGER!

Extremely flammable aerosol.  
Contains gas under pressure; may explode if heated.  
May be harmful if swallowed.  
Causes serious eye irritation.  
May cause drowsiness or dizziness

**FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL CHEMTREC-DAY OR NIGHT 1-800-424-9300.**

**CONTAINS:** Lubricating greases (74869-21-9), Solvent naphtha (64742-88-7), Molybdenum sulfide (1317-33-5), Copper Flake (7440-50-8). For more ingredient information, visit [rectorseal.com](http://rectorseal.com). **Precautionary Statements -PREVENTION:** Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not handle until all safety precautions have been read and understood. Wear gloves/protective clothing/eye protection/face protection. Wash hands thoroughly after handling. **RESPONSE:** If exposed or concerned: Get medical advice. **IF ON SKIN:** Wash with plenty of water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call a Doctor if you feel unwell. **IF SWALLOWED:** Do not induce vomiting. Call physician immediately. **STORAGE:** Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. **DISPOSAL:** Dispose of contents/container to an approved waste disposal plant. **KEEP OUT OF REACH OF CHILDREN.**

For additional information, refer to Safety Data Sheet, or Call Toll Free 1-800-231-3345.

## Limited Warranty

RectorSeal, LLC makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RectorSeal, LLC. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal, LLC shall not be liable for incidental or consequential damages.

Manufactured for

**RectorSeal, LLC**

**2601 Spenwick Drive • Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • [rectorseal.com](http://rectorseal.com)**

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2020 RectorSeal. All rights reserved. R50636-0820