



A CSW Industrials Company

# ZIPP™

Quick drying safe degreaser

## Description

ZIPP™ is a quick drying safe solvent degreaser that instantly removes grease, oil, waxes, tar, gums, grime, dirt, carbon, greasy stains, bilge slime and similar soils from most hard surfaces. It may be used on oil burner parts, compressors, refrigeration units, greasy fan blades, strainers, engines, stoves, relay contact points and electrical equipment. **It will not short out electrical equipment.**

## Characteristics | Features

- Non-flammable
- Non-conductive
- Excellent cleaner/degreaser
- Fast Drying
- Leaves no residue

## Applications

ZIPP™ may be used to degrease and clean oil burner parts, compressors, refrigeration units, strainers, engines, stoves, fan blades, relay contact parts and electrical equipment.

## Packaging

Code	Size	Qty. per Case	Lbs. per Case	Cubic Feet per Case
82642	14 ounce aerosol	12	14	0.52

## Instructions

**READ ALL DIRECTIONS, SDS AND WARNINGS ON LABEL BEFORE USING**

**DO NOT USE ON PLASTICS WITHOUT TESTING FIRST**

- For best results, use only on cool surfaces. Shake can well.
- Thoroughly saturate part(s) to be cleaned.
- Spray on small parts with light oil or grease films and on contact points on relays, motors, thermostats, and in all electrical or mechanical equipment.
- For heavy grease and grime deposits allow 5 minutes soaking time. Some agitation with brush or rag is very helpful
- Allow to air dry

**For additional technical information, call Toll Free 1-800-231-3345**

## Precautions

**FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT,  
CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300**

**WARNING!**

CAUSES SKIN AND SERIOUS EYE IRRITATION

MAY CAUSE RESPIRATORY IRRITATION

HARMFUL IF SWALLOWED

**KEEP OUT OF REACH OF CHILDREN**

**Read other precautions on back panel.**

**CONTAINS: Perchloroethylene and Methylene Chloride.** Contains gas under pressure; may explode if heated. Suspected of causing cancer. May cause an allergic skin reaction. May cause drowsiness or dizziness. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves and eye protection. Wash hands thoroughly after handling. Avoid breathing spray. Use only outdoors or in a well-ventilated place. Contaminated work clothing must not be allowed out of the workplace. Specific treatment (see FIRST AID section on this label). Protect from sunlight. Store locked up in a well-ventilated place. Dispose of container in accordance with local regulations.

**FIRST AID:** Get medical advice. **IF ON SKIN:** Wash with plenty of water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.



**WARNING:** This product can expose you to chemicals including Perchloroethylene and Methylene Chloride which is known to the State of California to cause cancer and other reproductive harm. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**For additional information, refer to Safety Data Sheet.**

## Specifications

Wt/Gal @ 77°F	11.99 lbs/ gal.
Flash Point SETA CC	None
Color	Clear liquid
Shelf Life	2 years minimum

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

## Limited Warranty

RectorSeal, LLC makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL, LLC. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal, LLC shall not be liable for incidental or consequential damages.

Manufactured by **RectorSeal® LLC** · 2601 Spenwick Drive, Houston, TX 77055, USA · 800-231-3345 · Fax 800-441-0051 · [rectorseal.com](http://rectorseal.com)

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2018 RectorSeal. All rights reserved. R50192-0518