

A CSW Industrials Company

PRODUCT DATA SHEET

FALCON WATER CONNECTIONS

Helical Water Connectors

Description

Falcon corrugated stainless steel water connector is a flexible tube that is used to connect water appliances to water supply lines. It is made of high-quality 304 stainless steel helical tube construction with chrome plated brass nuts. In addition to being durable and long-lasting, corrugated stainless steel water connectors are easy to install and require no special tools. The Super-Flex connecters offer a full 3/4" I.D. for increased flow when required.

These connectors are ideal for use in residential and commercial applications and are designed to withstand high pressure and temperature fluctuations. The chrome plated brass nuts at either end of the connector provide a secure and leak-proof connection to the water supply line.

Application

Flexible stainless steel tube for connecting water supply lines to water appliances.

- 250 Maximum PSI
- -40°F to 180°F

Recommended Use

- Water Heaters
- Mini Tankless Water Heaters
- · Water Softeners



Characteristics | Features

- 304 Series stainless steel
- Maintains optimal flow with full port design
- 100% leak tested
- Chrome plated brass nuts
- High temp EPDM washer chlorine and chloramine resistant



Approvals

- Complies to ASME A112.18.6-2017
- Complies to CSA B125.6-2017
- · ICC listed, tested & pertified
- UPC, IPC, NPC, IRC pompliant
- Complies to Minnesota plumbing code
- NSF 61 compliant
- NSF 372 compliant

FALCON WATER CONNECTIONS

Helical Water Connectors

Packaging

Code	Description	Qty per Case	Lbs per Case	Cubic Feet
1/2" ID Water Connect	tor			
S0212	1/2" I.D. SS Flex with 1/2" FIP X 1/2" FIP X 12"	25	5.13	0.21
S0216	1/2" I.D. SS Flex with 1/2" FIP X 1/2" FIP X 16"	25	5.62	0.28
S0220	1/2" I.D. SS Flex with 1/2" FIP X 1/2" FIP X 20"	25	6.94	0.35
S0230	1/2" I.D. SS Flex with 1/2" FIP X 1/2" FIP X 30"	25	9.09	0.51
S0236	1/2" I.D. SS Flex with 1/2" FIP X 1/2" FIP X 36"	25	9.48	0.62
GEN-U-Flex - 3/4" OD	Water Connectors	·		
GFF030418	3/4" O.D. SS Flex with 3/4" FIP X 3/4" FIP X 18"	25	8.16	0.43
GFF030424	3/4" O.D. SS Flex with 3/4" FIP X 3/4" FIP X 24"	25	9.59	0.56
Super-Flex - 3/4" ID W	/ater Connectors			
FF12	3/4" I.D. SS Flex with 3/4" FIP X 3/4" FIP X 12"	25	7.33	0.29
FF15	3/4" I.D. SS Flex with 3/4" FIP X 3/4" FIP X 15"	25	7.61	0.36
FF18	3/4" I.D. SS Flex with 3/4" FIP X 3/4" FIP X 18"	25	8.49	0.43
FF24	3/4" I.D. SS Flex with 3/4" FIP X 3/4" FIP X 24"	25	10.03	0.56
FF36	3/4" I.D. SS Flex with 3/4" FIP X 3/4" FIP X 36"	25	13.67	0.84
FF48	3/4" I.D. SS Flex with 3/4" FIP X 3/4" FIP X 48"	25	16.87	1.11
FF60	3/4" I.D. SS Flex with 3/4" FIP X 3/4" FIP X 60"	25	20.17	1.39
SWC13418	3/4" I.D. SS Flex with 1" FIP X 3/4" FIP X 18"	25	10.36	2.57
SWC13424	3/4" I.D. SS Flex with 1" FIP X 3/4" FIP X 24"	25	11.90	0.74



WARNING • This product can expose you to chemicals including Nickel, which is known to the State of California to cause cancer, birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

Lifetime Warranty



For more information on our product warranty, visit RectorSeal.com $\,$

Manufactured by

RectorSeal, LLC

2601 Spenwick Drive, Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • rectorseal.com PO Box 5266, Brendale, Qld 4500, Australia • 1300 772 878 • rectorseal.com.au 3255 Wyandotte St. East, Windsor, ON N8Y 1E9, Canada • 519-966-4901