

PRODUCT DATA SHEET

FALCON WATER CONNECTIONS

Push to Connect Water Connectors

Description

Falcon corrugated stainless steel water connector is a flexible tube that is used to connect water appliances to water supply lines. It is made of high-quality 304 stainless steel tube construction with chrome plated brass nuts. The Push to Connect design provides a quick installation to Copper, CPVC, and PEX tubing. In addition to being durable and long-lasting, corrugated stainless steel water connectors are easy to install and require no special tools.

These connectors are ideal for use in residential and commercial applications and are designed to withstand high pressure and temperature fluctuations. The chrome plated brass nuts at either end of the connector provide a secure and leak-proof connection to the water supply line. Please follow the installation instruction on product label when using these connectors.

Application

Flexible stainless steel tube for connecting water supply lines to water appliances.

- 250 Maximum PSI
- -40° F to 180° F

Recommended Use

Water Heaters

Water Softeners



Characteristics | Features

• 304 Series stainless steel

- Maintains optimal flow with full port design
- 100% leak tested
- Chrome plated brass nuts
- High temp EPDM washer chlorine and chloramine resistant



Approvals

- Complies to ASME A112.18.6-2017
- Complies to CSA B125.6-2017
- ICC listed, tested & certified
- UPC, IPC, NPC, IRC compliant
- Complies to Minnesota plumbing code
- NSF 61 compliant
- NSF 372 compliant

FALCON WATER CONNECTIONS

Push to Connect Water Connectors

Packaging

Code	Description	Qty per Case	Lbs per Case	Cubic Feet
Push to Connect Water	Connectors			
PTCPTC3418A	3/4" I.D. SS Flex with 3/4" JG PTC X 3/4" JG PTC X 18"	25	16.76	0.58
PTC34JG18A	3/4" I.D. SS Flex with 3/4" JG PTC X 3/4" FIP X 18"	25	14.22	0.50
PTC34JG24A	3/4" I.D. SS Flex with 3/4" JG PTC X 3/4" FIP X 24"	25	15.27	0.65
PTCFIPV18A	3/4" I.D. SS Flex with 3/4" PTCBALL VLV X 3/4" FIP X 18"	25	24.90	1.00
PTCFIPV24A	3/4" I.D. SS Flex with 3/4" PTCBALL VLV X 3/4" FIP X 24"	25	29.00	1.25
PTC34JGCLKQC18A	3/4" I.D. SS Flex with 3/4" JG PTC X Clack QC X 18"	25	18.19	0.54
PTC34JGCLKQC24A	3/4" I.D. SS Flex with 3/4" JG PTC X Clack QC X 24"	25	19.84	0.70
PTC34JG1N18A	3/4" I.D. SS Flex with 3/4" JG PTC X 1" nylon FIP X 18"	25	13.61	0.68
PTC34JG1N24A	3/4" I.D. SS Flex with 3/4" JG PTC X 1" nylon FIP X 24"	25	11.52	0.90
PTC34JG114N18A	3/4" I.D. SS Flex with 3/4" JG PTC X 1-1/4" nylon FIP X 18"	25	16.20	0.99
PTC1JG1N18A	1" I.D. SS Flex with 1" JG PTC X 1" nylon FIP X 18"	25	17.42	0.84
PTC1JG1N24A	1" I.D. SS Flex with 1" JG PTC X 1" nylon FIP X 24"	25	20.39	1.10
PTC1JGCLKQC18A	1" I.D. SS Flex with 1" JG PTC X Clack QC X 18"	25	20.50	0.63
PTC1JGCLKQC24A	1" I.D. SS Flex with 1" JG PTC X Clack QC X 24"	25	20.83	0.82
PTC1JG114N18A	1" I.D. SS Flex with 1" JG PTC X 1-1/4" nylon FIP X 18"	25	21.94	1.07
PTC1JG114N24A	1" I.D. SS Flex with 1" JG PTC X 1-1/4" nylon FIP X 24"	25	22.27	1.41

WARNING • This product can expose you to chemicals including Nickel, which is known to the State of California to cause cancer, birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

Lifetime Warranty



For more information on our product warranty, visit RectorSeal.com

Manufactured by

RectorSeal, LLC 2601 Spenwick Drive, Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • rectorseal.com PO Box 5266, Brendale, Qld 4500, Australia • 1300 772 878 • rectorseal.com.au 3255 Wyandotte St. East, Windsor, ON N8Y 1E9, Canada • 519-966-4901

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensors and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2023 RectorSeal. All rights reserved. R51047-0823