SATCO" NUVO"

Project Name

Location

Prepared By



NUVO 60-7354

RYDER 6 LIGHT CHANDELIER

Notes

[www] 11-14-2021 22:13:42

| General | |
|---|--|
| Status | Active |
| Collection | Ryder |
| Finish | Black / Polished Nickel |
| Style | Industrial |
| Number of Lamps | 6 |
| Height (in.) | 15.00 |
| Width (in.) | 25.25 |
| Indoor or Outdoor Fixture | Indoor |
| Specifications | |
| Base | Medium |
| Bulb Type | Incandescent |
| Max Wattage | 60W |
| Voltage | 120V |
| Bulb Included | No |
| Glass Description | Not Applicable |
| Fabric Description | N/A |
| Weight (lb.) | 1.40 |
| Sloped Ceiling | No |
| Fixture Type | Chandelier |
| Fixture Material | Steel |
| Dimensions | |
| | |
| Back Plate or Canopy Height (in.) | 0.79 |
| Back Plate or Canopy Height (in.) Back Plate or Canopy Diameter (in.) | 0.79 4.50 |
| Back Plate or Canopy Diameter | |
| Back Plate or Canopy Diameter (in.) | 4.50 |
| Back Plate or Canopy Diameter (in.) Stem Length | 4.50 |
| Back Plate or Canopy Diameter (in.) Stem Length Compliance | 4.50 36 in. |
| Back Plate or Canopy Diameter (in.) Stem Length Compliance Safety Listing | 4.50 36 in. cETLus |
| Back Plate or Canopy Diameter (in.) Stem Length Compliance Safety Listing Location Rating | 4.50 36 in. cETLus Dry |
| Back Plate or Canopy Diameter (in.) Stem Length Compliance Safety Listing Location Rating UL Application | 4.50 36 in. cETLus Dry Ceiling |
| Back Plate or Canopy Diameter (in.) Stem Length Compliance Safety Listing Location Rating UL Application Energy Star | 4.50 36 in. cETLus Dry Ceiling No |
| Back Plate or Canopy Diameter (in.) Stem Length Compliance Safety Listing Location Rating UL Application Energy Star California Prop 65 | 4.50 36 in. CETLus Dry Ceiling No Lead |
| Back Plate or Canopy Diameter (in.) Stem Length Compliance Safety Listing Location Rating UL Application Energy Star California Prop 65 RoHS Compliant | 4.50 36 in. CETLus Dry Ceiling No Lead |
| Back Plate or Canopy Diameter (in.) Stem Length Compliance Safety Listing Location Rating UL Application Energy Star California Prop 65 RoHS Compliant Additional Information | 4.50 36 in. CETLus Dry Ceiling No Lead Yes 30 degree swivel for sloped ceilings; Light Direction-Multiple |

For More Information Visit: <u>http://www.satco.com/</u>

