SATCO NUVO

Project Name

Location

Prepared By



......3 00 00 0000 00.50.4

Additional Information

Additional Information

Specification Note

Warranty

Status			
Substitute 65-537R1 Fixture Type Flood Light Finish Bronze Wattage 50W Lumen Output 5717L CCT (Kelvin) 3000K Temperature Warm White IP Rating IP65 Indoor or Outdoor Fixture Outdoor Specifications Technology LED CRI 80+ Voltage 100V-277V Beam Angle 130 Rated Hours 50000 Operating Temperature -20C (-4F) to +45C (+113F) Dimmable Non-Dimmable Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Weight (lb.) 3.62 Material Die Cast Aluminum Dimensions Height (in.) 2.13 Width (in.) 10.16 Length (in.) 8.50 Compliance Safety Listing CULus - Listed Location Rating	General		
Fixture Type Flood Light Finish Bronze Wattage 50W Lumen Output 5717L CCT (Kelvin) 3000K Temperature Warm White IP Rating IP65 Indoor or Outdoor Fixture Outdoor Specifications Technology LED CRI 80+ Voltage 100V-277V Beam Angle 130 Rated Hours 50000 Operating Temperature -20C (-4F) to +45C (+113F) Dimmable Non-Dimmable Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Weight (lb.) 3.62 Material Die Cast Aluminum Dimensions Height (in.) 2.13 Width (in.) 10.16 Length (in.) 8.50 Compliance Safety Listing CULus - Listed Location Rating Wet UL Application W	Status	Active	
Finish Bronze Wattage 50W Lumen Output 5717L CCT (Kelvin) 3000K Temperature Warm White IP Rating IP65 Indoor or Outdoor Fixture Outdoor Specifications Technology LED CRI 80+ Voltage 100V-277V Beam Angle 130 Rated Hours 50000 Operating Temperature -20C (-4F) to +45C (+113F) Dimmable Non-Dimmable Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Weight (lb.) 3.62 Material Die Cast Aluminum Dimensions Height (in.) 2.13 Width (in.) Dimensions Height (in.) 2.13 Width (in.) UL application Well Length (in.) 8.50 Compliance Safety Listing<	Substitute	65-537R1	
Wattage 50W Lumen Output 5717L CCT (Kelvin) 3000K Temperature Warm White IP Rating IP65 Indoor or Outdoor Fixture Outdoor Specifications Technology LED CRI 80+ Voltage 100V-277V Beam Angle 130 Rated Hours 50000 Operating Temperature -20C (-4F) to +45C (+113F) Dimmable Non-Dimmable Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Weight (lb.) 3.62 Material Die Cast Aluminum Dimensions Height (in.) 2.13 Width (in.) 10.16 Length (in.) 2.13 Width (in.) 10.16 Length (in.) 8.50 Compliance Safety Listing CULus - Listed Location Rating Wet UL Application Wall	Fixture Type	Flood Light	
Lumen Output	Finish	Bronze	
CCT (Kelvin) 3000K Temperature Warm White IP Rating IP65 Indoor or Outdoor Fixture Outdoor Specifications Technology LED CRI 80+ Voltage 100V-277V Beam Angle 130 Rated Hours 50000 Operating Temperature -20C (-4F) to +45C (+113F) Dimmable Non-Dimmable Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Weight (lb.) 3.62 Material Die Cast Aluminum Dimensions Height (in.) 2.13 Width (in.) Width (in.) 10.16 Length (in.) 8.50 Compliance Safety Listing cULus - Listed Location Rating Wet UL Application Wall Energy Star No DLC Approved No IC Rated Yes	Wattage	50W	
Temperature	Lumen Output	5717L	
PRating	CCT (Kelvin)	3000K	
Indoor or Outdoor Fixture Specifications Technology CRI 80+ Voltage 100V-277V Beam Angle 130 Rated Hours 50000 Operating Temperature -20C (-4F) to +45C (+113F) Dimmable Non-Dimmable Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Weight (lb.) 3.62 Material Dimensions Height (in.) 2.13 Width (in.) 10.16 Length (in.) 8.50 Compliance Safety Listing CULus - Listed Ucation Rating Wet UL Application Energy Star No DLC Approved No IC Rated Yes California T24 2016 - 2022 JA8 Compliant; T20 Exempt - Fixtures Not Regulated California Status California T24 Compliant Title 20 / 24 Status California T24 Compliant California T24 Compliant California Prop 65 Lead ROHS Compliant Yes FCC Compliant	Temperature	Warm White	
Technology LED CRI 80+ Voltage 100V-277V Beam Angle 130 Rated Hours 50000 Operating Temperature -20C (-4F) to +45C (+113F) Dimmable Non-Dimmable Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Weight (lb.) 3.62 Material Dimensions Height (in.) 2.13 Width (in.) 10.16 Length (in.) 8.50 Compliance Safety Listing CULus - Listed Location Rating Wet UL Application Wall Energy Star No DLC Approved No IC Rated Yes CA T20 / T24 Rationale California T24 2016 - 2022 JA8 Compliant; T20 Exempt - Fixtures Not Regulated California Status Lawful for sale in California Title 20 / 24 Status California T24 Compliant California Prop 65 Lead ROHS Compliant Yes FCC Compliant Yes	IP Rating	IP65	
Technology LED CRI 80+ Voltage 100V-277V Beam Angle 130 Rated Hours 50000 Operating Temperature -20C (-4F) to +45C (+113F) Dimmable Non-Dimmable Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Weight (lb.) 3.62 Material Die Cast Aluminum Dimensions Height (in.) 2.13 Width (in.) 10.16 Length (in.) 8.50 Compliance Safety Listing CULus - Listed UL Application Wall Energy Star No DLC Approved No IC Rated Yes CA T20 / T24 Rationale California T24 2016 - 2022 JA8 CA T20 / T24 Rationale Compliant; T20 Exempt - Fixtures Not Regulated California Status Lawful for sale in California Title 20 / 24 Status California T24 Compliant California T24 Compliant Yes <td>Indoor or Outdoor Fixture</td> <td>Outdoor</td>	Indoor or Outdoor Fixture	Outdoor	
CRI 80+ Voltage 100V-277V Beam Angle 130 Rated Hours 50000 Operating Temperature -20C (-4F) to +45C (+113F) Dimmable Non-Dimmable Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Weight (lb.) 3.62 Material Die Cast Aluminum Dimensions Height (in.) 2.13 Width (in.) 10.16 Length (in.) 8.50 Compliance Safety Listing CULus - Listed Location Rating Wet UL Application Wall Energy Star No DLC Approved No IC Rated Yes California T24 2016 - 2022 JA8 CA T20 / T24 Rationale California T24 Compliant Title 20 / 24 Status California T24 Compliant California Prop 65 Lead ROHS Compliant Yes FCC Compliant Yes	Specifications		
CRI 80+ Voltage 100V-277V Beam Angle 130 Rated Hours 50000 Operating Temperature -20C (-4F) to +45C (+113F) Dimmable Non-Dimmable Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Weight (lb.) 3.62 Material Die Cast Aluminum Dimensions Height (in.) 2.13 Width (in.) 10.16 Length (in.) 8.50 Compliance Safety Listing CULus - Listed Location Rating Wet UL Application Wall Energy Star No DLC Approved No IC Rated Yes California T24 2016 - 2022 JA8 Compliant T24 2016 - 2022 JA8 Compliant T24 Status California T24 Compliant California Status Lawful for sale in California Title 20 / 24 Status California T24 Compliant California Prop 65 RoHS Compliant Yes FCC Compliant Yes	Technology	LED	
Beam Angle 130 Rated Hours 50000 Operating Temperature -20C (-4F) to +45C (+113F) Dimmable Non-Dimmable Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Weight (lb.) 3.62 Material Die Cast Aluminum Dimensions Height (in.) 2.13 Width (in.) 10.16 Length (in.) 8.50 Compliance Safety Listing CULus - Listed Location Rating Wet UL Application Wall Energy Star No DLC Approved No IC Rated Yes California T24 2016 - 2022 JA8 CA T20 / T24 Rationale California T24 Compliant Title 20 / 24 Status California T24 Compliant California Prop 65 Lead ROHS Compliant Yes FCC Compliant Yes		80+	
Beam Angle 130 Rated Hours 50000 Operating Temperature -20C (-4F) to +45C (+113F) Dimmable Non-Dimmable Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Weight (lb.) 3.62 Material Die Cast Aluminum Dimensions Height (in.) 2.13 Width (in.) 10.16 Length (in.) 8.50 Compliance Safety Listing CULus - Listed Location Rating Wet UL Application Wall Energy Star No DLC Approved No IC Rated Yes California T24 2016 - 2022 JA8 CA T20 / T24 Rationale California T24 Compliant Title 20 / 24 Status California T24 Compliant California Prop 65 Lead ROHS Compliant Yes FCC Compliant Yes	Voltage	100V-277V	
Operating Temperature Dimmable Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Weight (lb.) 3.62 Material Dimensions Height (in.) Length (in.) Compliance Safety Listing Location Rating UL Application Energy Star DLC Approved IC Rated CA T20 / T24 Rationale California Status Title 20 / 24 Status California T24 Compliant California T24 Compliant Tyes FCC Compliant Polycarbonate (PC) Built-in surge protection - 2KV Weight (lb.) 3.62 Die Cast Aluminum Dine Cast Aluminum Cultus - Listed Wet ULus - Listed Wet ULus - Listed Ves California T24 2016 - 2022 JA8 Compliant; T20 Exempt - Fixtures Not Regulated California T24 Compliant Title 20 / 24 Status California T24 Compliant Ves FCC Compliant Yes	Beam Angle	130	
Dimmable Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Weight (lb.) 3.62 Material Die Cast Aluminum Dimensions Height (in.) 2.13 Width (in.) Length (in.) 8.50 Compliance Safety Listing Location Rating UL Application Energy Star DLC Approved IC Rated Yes California T24 2016 - 2022 JA8 Compliant; T20 Exempt - Fixtures Not Regulated California Status Lawful for sale in California Title 20 / 24 Status California T24 Compliant California Prop 65 Lead RoHS Compliant Yes FCC Compliant	-	50000	
Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Weight (lb.) 3.62 Material Die Cast Aluminum Dimensions Height (in.) 2.13 Width (in.) 10.16 Length (in.) 8.50 Compliance Safety Listing CULus - Listed Location Rating Wet UL Application Wall Energy Star No DLC Approved No IC Rated Yes California T24 2016 - 2022 JA8 CA T20 / T24 Rationale Compliant; T20 Exempt - Fixtures Not Regulated California Status Lawful for sale in California Title 20 / 24 Status California T24 Compliant California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes	Operating Temperature	-20C (-4F) to +45C (+113F)	
Surge Protection Weight (lb.) 3.62 Material Die Cast Aluminum Dimensions Height (in.) Length (in.) Compliance Safety Listing Location Rating UL Application Energy Star DLC Approved IC Rated Yes California T24 2016 - 2022 JA8 Compliant; T20 Exempt - Fixtures Not Regulated California Status California T24 Compliant Title 20 / 24 Status California T24 Compliant		Non-Dimmable	
Weight (lb.)3.62MaterialDie Cast AluminumDimensionsHeight (in.)2.13Width (in.)10.16Length (in.)8.50ComplianceSafety ListingcULus - ListedLocation RatingWetUL ApplicationWallEnergy StarNoDLC ApprovedNoIC RatedYesCA T20 / T24 RationaleCalifornia T24 2016 - 2022 JA8 Compliant; T20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 CompliantCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYes	Lens Material		
Weight (lb.)3.62MaterialDie Cast AluminumDimensionsHeight (in.)2.13Width (in.)10.16Length (in.)8.50ComplianceSafety ListingcULus - ListedLocation RatingWetUL ApplicationWallEnergy StarNoDLC ApprovedNoIC RatedYesCA T20 / T24 RationaleCalifornia T24 2016 - 2022 JA8 Compliant; T20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 CompliantCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYes	Surge Protection		
Die Cast AluminumDimensionsHeight (in.)2.13Width (in.)10.16Length (in.)8.50ComplianceSafety ListingcULus - ListedLocation RatingWetUL ApplicationWallEnergy StarNoDLC ApprovedNoIC RatedYesCA T20 / T24 RationaleCalifornia T24 2016 - 2022 JA8 Compliant; T20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 CompliantCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYes			
Height (in.) Width (in.) Length (in.) Compliance Safety Listing CULus - Listed Location Rating Wet UL Application Energy Star DLC Approved IC Rated CA T20 / T24 Rationale California Status Title 20 / 24 Status California T24 Compliant California Prop 65 RoHS Compliant Yes 10.16 2.13 10.16 Louise CULus - Listed Wet Vet California - Listed Coulling Coulling Coulling California T24 2016 - 2022 JA8 Compliant; T20 Exempt - Fixtures Not Regulated California Status California T24 Compliant California Prop 65 Lead RoHS Compliant Yes FCC Compliant			
Width (in.) Length (in.) Response Safety Listing CULus - Listed Location Rating Wet UL Application Wall Energy Star No DLC Approved No IC Rated Yes California T24 2016 - 2022 JA8 CA T20 / T24 Rationale Compliant; T20 Exempt - Fixtures Not Regulated California Status Lawful for sale in California Title 20 / 24 Status California T24 Compliant California Prop 65 Lead RoHS Compliant Yes FCC Compliant	Dimensions		
Width (in.) Length (in.) Response Safety Listing CULus - Listed Location Rating Wet UL Application Wall Energy Star No DLC Approved No IC Rated Yes California T24 2016 - 2022 JA8 CA T20 / T24 Rationale Compliant; T20 Exempt - Fixtures Not Regulated California Status Lawful for sale in California Title 20 / 24 Status California T24 Compliant California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes	Height (in.)	2.13	
Length (in.) Compliance Safety Listing		10.16	
Safety Listing Location Rating Wet UL Application Energy Star DLC Approved IC Rated California T24 2016 - 2022 JA8 CAT20 / T24 Rationale California Status California Status California T24 Compliant California Prop 65 Lead RoHS Compliant Yes FCC Compliant		8.50	
Location Rating UL Application Energy Star No DLC Approved No IC Rated Yes California T24 2016 - 2022 JA8 CA T20 / T24 Rationale California Status California Status Lawful for sale in California Title 20 / 24 Status California T24 Compliant California T24 Compliant Yes FCC Compliant Yes	Compliance		
Location Rating UL Application Energy Star No DLC Approved No IC Rated Yes California T24 2016 - 2022 JA8 CA T20 / T24 Rationale California Status California Status Lawful for sale in California Title 20 / 24 Status California T24 Compliant California T24 Compliant Yes FCC Compliant Yes	Safety Listing	cULus - Listed	
Energy Star DLC Approved No IC Rated Yes California T24 2016 - 2022 JA8 CA T20 / T24 Rationale California Status California Status Lawful for sale in California Title 20 / 24 Status California T24 Compliant California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes		Wet	
DLC Approved IC Rated Yes California T24 2016 - 2022 JA8 Compliant; T20 Exempt - Fixtures Not Regulated California Status Lawful for sale in California Title 20 / 24 Status California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes	UL Application	Wall	
IC Rated Yes California T24 2016 - 2022 JA8 CA T20 / T24 Rationale California T24 2016 - 2022 JA8 Compliant; T20 Exempt - Fixtures Not Regulated California Status Lawful for sale in California Title 20 / 24 Status California T24 Compliant California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes	Energy Star	No	
California T24 2016 - 2022 JA8 Compliant; T20 Exempt - Fixtures Not Regulated California Status Lawful for sale in California Title 20 / 24 Status California T24 Compliant California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes	DLC Approved	No	
CA T20 / T24 Rationale Compliant; T20 Exempt - Fixtures Not Regulated California Status Lawful for sale in California Title 20 / 24 Status California T24 Compliant California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes	IC Rated	Yes	
Title 20 / 24 Status California T24 Compliant California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes	CA T20 / T24 Rationale	Compliant; T20 Exempt - Fixtures	
California Prop 65 RoHS Compliant FCC Compliant Yes Yes	California Status	Lawful for sale in California	
RoHS Compliant Yes FCC Compliant Yes	Title 20 / 24 Status	California T24 Compliant	
FCC Compliant Yes	California Prop 65	Lead	
	RoHS Compliant	Yes	
SDS Sheet LED_Fixture	FCC Compliant	Yes	
	SDS Sheet	LED_Fixture	

1/2" Thread knuckle mount
Adjustable Angle from 0 to 90

5 Year Limited - Fixtures

degrees

For More Information Visit: http://www.satco.com/







