

Project Name

Location

Prepared By



SATCO S11451

5A19/LED/830/120V/D/4PK

Notes

[www] 05-14-2022 01:49:14

General

| | |
|-------------------------|--------------|
| Status | Active |
| Watts | 5W |
| Incandescent Equivalent | 40W |
| Volts | 120V |
| Shape | A19 |
| Base | Medium |
| ANSI Base | E26 |
| Finish | Frost |
| CCT (Kelvin) | 3000K |
| Temperature | Soft White |
| CRI | 80 |
| Lumens | 450L |
| Beam Spread | 230 |
| Dimmable | Yes-Dimmable |
| Hours Rated | 15000 |
| Lamp Type | Type A |
| Technology | LED |

Electrical

| | |
|-----------------------|--|
| Operating Frequency | 60 Hz |
| Dimming Note | Dimming range from 100 to less than or equal to 20 percent depending on dimmer control |
| Operating Temperature | -20C (-4F) to a maximum of +45C (+113F) |

Physical

| | |
|---------------|-------|
| MOL | 4.17 |
| MOD | 2.38 |
| Housing Color | White |
| Weight (lb.) | 0.31 |

Additional Information

| | |
|----------------------------|----------------|
| Rated For Enclosed Fixture | Yes |
| Warranty | 3 Year Limited |

Compliance

| | |
|------------------------|--------------------------------------|
| Safety Listing | cULus - Listed |
| Location Rating | Damp |
| Energy Star | Pending |
| CA T20 / T24 Rationale | Non-Compliant - Efficacy Rating <297 |
| RoHS Compliant | Yes |
| SDS Sheet | LED_Lamp |