

Project Name

Location

Prepared By



SATCO S11742

9.5/T8/LED/48-840/DR

Notes

[www] 01-17-2022 02:16:05

General

| | |
|------------------------|-----------------|
| Status | Active |
| Watts | 9.5W |
| Fluorescent Equivalent | 32W/30W/28W/25W |
| Volts | 120V-277V |
| Ballast Type | Type A |
| Shape | T8 |
| Base | Medium Bi Pin |
| ANSI Base | G13 |
| Nominal Length | 48.00 |
| Finish | Gloss |
| CCT (Kelvin) | 4000K |
| Temperature | Cool White |
| CRI | 82 |
| Lumens | 1740L |
| Beam Spread | 210 |
| Dimmable | Yes-Dimmable |
| Hours Rated | 50000 |
| Lamp Type | Linear |
| Technology | LED |

Electrical

| | |
|-------------------------|--|
| Ballasting Requirements | Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart |
| Operating Frequency | 50/60 Hz |
| Dimming Note | Check Ballast MFG for Dimmer Compatibility; Only in Type A mode; Dimming range from 100 to less than or equal to 20 percent depending on dimmer control |
| Power Factor | 0.9 |
| THD | 20% |
| Operating Temperature | -20C (-4F) to a maximum of +45C (+113F) |

Physical

| | |
|---------------|-------|
| MOL | 48.00 |
| MOD | 1.00 |
| Material | Glass |
| Housing Color | White |
| Weight (lb.) | 0.42 |

Additional Information

| | |
|--------------------|-------------------------------|
| Specification Note | Surge Protection |
| Warranty | 5 Year Limited - T8 LED Bulbs |

Compliance

| | |
|-----------------|-------|
| Safety Listing | cULus |
| Location Rating | Damp |
| Energy Star | No |
| DLC Approved | Yes |

| | |
|-------------------|-----------------|
| DLC ID | PLRBCA9H3Z8T |
| California Status | Lawful for sale |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| NSF Approved | Yes |

Copyright 2020 Satco Products, Inc.
All Rights Reserved

For More Information Visit:
<http://www.satco.com/>

