

Project Name

Location Prepared By



SATCO S11911

11.5T8/LED/48-835/BP 120-277V

Notes

General	
Status	Active
Watts	11.5W
Fluorescent Equivalent	32W
Volts	120V-277V
Ballast Type	Туре В
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48.00
Finish	Frost
CCT (Kelvin)	3500
Temperature	Neutral White
CRI	80
Lumens	1650L
Beam Spread	180
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED
Electrical	
Ballasting Requirements	Ballast Bypass; Direct wire 120- 277V line voltage; No ballast or external driver required
Operating Frequency	50/60 Hz
Power Factor	0.9
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)
Physical	
MOL	<i>1</i> 7 78
MOL	47.78
MOD	1
MOD Material	1 Glass
MOD Material Lens Finish	1 Glass Frost
MOD Material Lens Finish Lens Material	1 Glass Frost Glass
MOD Material Lens Finish Lens Material Housing Color	1 Glass Frost Glass White
MOD Material Lens Finish Lens Material	1 Glass Frost Glass
MOD Material Lens Finish Lens Material Housing Color	1 Glass Frost Glass White
MOD Material Lens Finish Lens Material Housing Color Weight (lb.)	1 Glass Frost Glass White
MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	1 Glass Frost Glass White 0.85 Installation protection - will not light
MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	1 Glass Frost Glass White 0.85 Installation protection - will not light if ballast is not bypassed.
MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info	1 Glass Frost Glass White 0.85 Installation protection - will not light if ballast is not bypassed. PET Coated Two Installation Options - 1. Double Ended Wiring or 2. Single
MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Shatter-Proof Type Installation Notes	Glass Frost Glass White 0.85 Installation protection - will not light if ballast is not bypassed. PET Coated Two Installation Options - 1. Double Ended Wiring or 2. Single Ended Wiring 5 Year Limited - T8 LED Bulbs -
MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Shatter-Proof Type Installation Notes Warranty Compliance	Glass Frost Glass White 0.85 Installation protection - will not light if ballast is not bypassed. PET Coated Two Installation Options - 1. Double Ended Wiring or 2. Single Ended Wiring 5 Year Limited - T8 LED Bulbs -
MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Shatter-Proof Type Installation Notes Warranty	Glass Frost Glass White 0.85 Installation protection - will not light if ballast is not bypassed. PET Coated Two Installation Options - 1. Double Ended Wiring or 2. Single Ended Wiring 5 Year Limited - T8 LED Bulbs - Ballast Bypass
MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Shatter-Proof Type Installation Notes Warranty Compliance Safety Listing Location Rating	Glass Frost Glass White 0.85 Installation protection - will not light if ballast is not bypassed. PET Coated Two Installation Options - 1. Double Ended Wiring or 2. Single Ended Wiring 5 Year Limited - T8 LED Bulbs - Ballast Bypass cULus Classified
MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Shatter-Proof Type Installation Notes Warranty Compliance Safety Listing Location Rating Energy Star	1 Glass Frost Glass White 0.85 Installation protection - will not light if ballast is not bypassed. PET Coated Two Installation Options - 1. Double Ended Wiring or 2. Single Ended Wiring 5 Year Limited - T8 LED Bulbs - Ballast Bypass cULus Classified Damp
MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Shatter-Proof Type Installation Notes Warranty Compliance Safety Listing Location Rating	Glass Frost Glass White 0.85 Installation protection - will not light if ballast is not bypassed. PET Coated Two Installation Options - 1. Double Ended Wiring or 2. Single Ended Wiring 5 Year Limited - T8 LED Bulbs - Ballast Bypass cULus Classified Damp No

California Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	ETL Sanitation listed (conforms to NSF)

Copyright 2020 Satco Products, Inc. All Rights Reserved

For More Information Visit: http://www.satco.com/







