

SATCO S1191618.5T8/LED/48-840/BP 120-277V

Notes

1000年1月

General	
Otation	A akin sa
Status Watts	Active 18.5W
Fluorescent Equivalent	32W
Volts	120V-277V
Ballast Type	Type B
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48.00
Finish	Frost
CCT (Kelvin)	4000
Temperature	Cool White
CRI	80
Lumens	2500L
Beam Spread	180
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED
Electrical	
Ballasting Requirements	Ballast Bypass; Direct wire 120- 277V line voltage; No ballast or external driver required
Power Factor	0.92
On a ratio a Tampa ratura	-20C (-4F) to a maximum of +45C
Operating Temperature	(+113F)
Physical	
Physical	(+113F)
Physical MOL	(+113F) 47.78
Physical MOL MOD	(+113F) 47.78 1
Physical MOL MOD Material	(+113F) 47.78 1 Glass
Physical MOL MOD Material Lens Finish	(+113F) 47.78 1 Glass Frost
Physical MOL MOD Material Lens Finish Lens Material	(+113F) 47.78 1 Glass Frost Glass
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.)	(+113F) 47.78 1 Glass Frost Glass White
Physical MOL MOD Material Lens Finish Lens Material Housing Color	(+113F) 47.78 1 Glass Frost Glass White 0.85
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.)	(+113F) 47.78 1 Glass Frost Glass White 0.85 Installation protection - will not light
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	(+113F) 47.78 1 Glass Frost Glass White 0.85 Installation protection - will not light if ballast is not bypassed.
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	(+113F) 47.78 1 Glass Frost Glass White 0.85 Installation protection - will not light
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info	(+113F) 47.78 1 Glass Frost Glass White 0.85 Installation protection - will not light if ballast is not bypassed. PET Coated Two Installation Options - 1. Double Ended Wiring or 2. Single
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Shatter-Proof Type Installation Notes	(+113F) 47.78 1 Glass Frost Glass White 0.85 Installation protection - will not light if ballast is not bypassed. PET Coated Two Installation Options - 1. Double Ended Wiring or 2. Single Ended Wiring 5 Year Limited - T8 LED Bulbs -
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Shatter-Proof Type Installation Notes Warranty	(+113F) 47.78 1 Glass Frost Glass White 0.85 Installation protection - will not light if ballast is not bypassed. PET Coated Two Installation Options - 1. Double Ended Wiring or 2. Single Ended Wiring 5 Year Limited - T8 LED Bulbs -
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Shatter-Proof Type Installation Notes Warranty Compliance	(+113F) 47.78 1 Glass Frost Glass White 0.85 Installation protection - will not light if ballast is not bypassed. PET Coated Two Installation Options - 1. Double Ended Wiring or 2. Single Ended Wiring 5 Year Limited - T8 LED Bulbs - Ballast Bypass
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Shatter-Proof Type Installation Notes Warranty Compliance Safety Listing	(+113F) 47.78 1 Glass Frost Glass White 0.85 Installation protection - will not light if ballast is not bypassed. PET Coated Two Installation Options - 1. Double Ended Wiring or 2. Single Ended Wiring 5 Year Limited - T8 LED Bulbs - Ballast Bypass cULus Classified
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Shatter-Proof Type Installation Notes Warranty Compliance Safety Listing Location Rating	(+113F) 47.78 1 Glass Frost Glass White 0.85 Installation protection - will not light if ballast is not bypassed. PET Coated Two Installation Options - 1. Double Ended Wiring or 2. Single Ended Wiring 5 Year Limited - T8 LED Bulbs - Ballast Bypass cUlcus Classified Damp
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Shatter-Proof Type Installation Notes Warranty Compliance Safety Listing Location Rating Energy Star	(+113F) 47.78 1 Glass Frost Glass White 0.85 Installation protection - will not light if ballast is not bypassed. PET Coated Two Installation Options - 1. Double Ended Wiring or 2. Single Ended Wiring 5 Year Limited - T8 LED Bulbs - Ballast Bypass cULus Classified Damp No
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Shatter-Proof Type Installation Notes Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved	(+113F) 47.78 1 Glass Frost Glass White 0.85 Installation protection - will not light if ballast is not bypassed. PET Coated Two Installation Options - 1. Double Ended Wiring or 2. Single Ended Wiring 5 Year Limited - T8 LED Bulbs - Ballast Bypass cULus Classified Damp No Yes

RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	ETL Sanitation listed (conforms to NSF)

Copyright 2020 Satco Products, Inc. All Rights Reserved

For More Information Visit: http://www.satco.com/







