SATCO" NUVO"

Project Name

Location

Prepared By



SATCO S11920

13.5T8/LED/48-830/DIM-BP

Notes

[www] 10-11-2021 02:06:30

General	
Status	Active
Watts	13.5W
Volts	120V
Ballast Type	Туре В
Shape	Т8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48.00
Finish	Frost
CCT (Kelvin)	3000
Temperature	Warm White
CRI	82
Lumens	1700L
Beam Spread	220
Dimmable	Yes-Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED
Electrical	
Ballasting Requirements	Ballast Bypass; Direct wire 120V line voltage; No ballast or external
Dallasting nequilements	driver required
Dimming Tuno	Reverse Phase or Phase
Dimming Type	Selectable
Power Factor	0.9
Operating Temperature	-20C (-4F) to a maximum of +45C
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)
Operating Temperature Physical	
Physical	(+113F)
Physical MOL	(+113F) 47.78
Physical MOL MOD	(+113F) 47.78 1
Physical MOL MOD Material	(+113F) 47.78 1 Glass
Physical MOL MOD Material Lens Finish	(+113F) 47.78 1 Glass Frost
Physical MOL MOD Material Lens Finish Lens Material Housing Color	(+113F) 47.78 1 Glass Frost Glass
Physical MOL MOD Material Lens Finish Lens Material Housing Color Additional Information	(+113F) 47.78 1 Glass Frost Glass White
Physical MOL MOD Material Lens Finish Lens Material Housing Color	(+113F) 47.78 1 Glass Frost Glass
Physical MOL MOD Material Lens Finish Lens Material Housing Color Additional Information	(+113F) 47.78 1 Glass Frost Glass White All glass tube Approved for use with tube guards
Physical MOL MOD Material Lens Finish Lens Material Housing Color Additional Information Additional Info	(+113F) 47.78 1 Glass Frost Glass White All glass tube
Physical MOL MOD Material Lens Finish Lens Material Housing Color Additional Information Additional Info Tube Guard Use	(+113F) 47.78 1 Glass Frost Glass White All glass tube All glass tube Install only in non-shunted lampholders 5 Year Limited - T8 LED Bulbs -
Physical MOL MOD Material Lens Finish Lens Material Housing Color Additional Information Additional Info Tube Guard Use Installation Notes Warranty	(+113F) 47.78 1 Glass Frost Glass White All glass tube Approved for use with tube guards Install only in non-shunted lampholders
Physical MOL MOD Material Lens Finish Lens Material Housing Color Additional Information Additional Info Tube Guard Use Installation Notes Warranty Compliance	(+113F) 47.78 1 Glass Frost Glass White All glass tube Approved for use with tube guards Install only in non-shunted lampholders 5 Year Limited - T8 LED Bulbs - Ballast Bypass
Physical MOL MOD Material Lens Finish Lens Material Housing Color Additional Information Additional Info Tube Guard Use Installation Notes Warranty Compliance Safety Listing	(+113F) 47.78 1 Glass Frost Glass White All glass tube Approved for use with tube guards Install only in non-shunted lampholders 5 Year Limited - T8 LED Bulbs - Ballast Bypass
Physical MOL MOD Material Lens Finish Lens Material Housing Color Additional Information Additional Info Tube Guard Use Installation Notes Warranty Compliance Safety Listing Location Rating	(+113F) 47.78 1 Glass Frost Glass White All glass tube All glass tube Approved for use with tube guards Install only in non-shunted lampholders 5 Year Limited - T8 LED Bulbs - Ballast Bypass cULus Classified Damp
Physical MOL MOD Material Lens Finish Lens Material Housing Color Additional Information Additional Info Tube Guard Use Installation Notes Warranty Compliance Safety Listing Location Rating Energy Star	(+113F) 47.78 1 Glass Frost Glass White All glass tube Approved for use with tube guards Install only in non-shunted lampholders 5 Year Limited - T8 LED Bulbs - Ballast Bypass CULus Classified Damp No
Physical MOL MOD Material Lens Finish Lens Material Housing Color Additional Information Additional Info Tube Guard Use Installation Notes Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved	(+113F) 47.78 1 Glass Frost Glass White All glass tube Approved for use with tube guards Install only in non-shunted lampholders 5 Year Limited - T8 LED Bulbs - Ballast Bypass CULus Classified Damp No Yes
Physical MOL MOD Material Lens Finish Lens Material Housing Color Additional Information Additional Info Tube Guard Use Installation Notes Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved DLC ID	(+113F) 47.78 1 Glass Frost Glass White All glass tube All glass tube All glass tube Solution Solution Install only in non-shunted lampholders 5 Year Limited - T8 LED Bulbs - Ballast Bypass CULus Classified Damp No Yes PLV12B1YBIYP
Physical MOL MOD Material Lens Finish Lens Material Housing Color Additional Information Additional Info Tube Guard Use Installation Notes Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved DLC ID California Status	(+113F) 47.78 1 Glass Frost Glass White All glass tube All glass tube Approved for use with tube guards Install only in non-shunted lampholders 5 Year Limited - T8 LED Bulbs - Ballast Bypass CULus Classified Damp No Yes PLV12B1YBIYP Lawful for sale
Physical MOL MOD Material Lens Finish Lens Material Housing Color Additional Information Additional Info Tube Guard Use Installation Notes Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved DLC ID	(+113F) 47.78 1 Glass Frost Glass White All glass tube All glass tube Approved for use with tube guards Install only in non-shunted lampholders 5 Year Limited - T8 LED Bulbs - Ballast Bypass CULus Classified Damp No Yes PLV12B1YBIYP Lawful for sale Yes
Physical MOL MOD Material Lens Finish Lens Material Housing Color Additional Information Additional Info Tube Guard Use Installation Notes Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved DLC ID California Status	(+113F) 47.78 1 Glass Frost Glass White All glass tube All glass tube Approved for use with tube guards Install only in non-shunted lampholders 5 Year Limited - T8 LED Bulbs - Ballast Bypass CULus Classified Damp No Yes PLV12B1YBIYP Lawful for sale

NSF Approved

Yes

Copyright 2020 Satco Products, Inc. All Rights Reserved

For More Information Visit: <u>http://www.satco.com/</u>

