SATCO' NUVO

Project Name

Location

Prepared By

SATCO S11937

11T8/LED/36-850/XD

Notes

S11937

General	
	• ··
Status	Active
Watts	11W
Fluorescent Equivalent	25W
Ballast Type	Туре С Т8
Shape	
ANSI Base	Medium Bi Pin
	G13
Nominal Length	36 For et
Finish	Frost
CCT (Kelvin)	5000
Temperature	Natural Light
CRI	82
Lumens	1600L
Beam Spread	220
Dimmable	Yes-Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED
Electrical	
Ballasting Requirements	Ballast replaced with external driver
Operating Frequency	50/60 Hz
Power Factor	0.9
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)
Operating Temperature Physical	. ,
Physical	(+113F)
Physical MOL	. ,
Physical MOL MOD	(+113F) <u>36</u> <u>1</u>
Physical MOL MOD Lens Finish	(+113F) 36
Physical MOL MOD Lens Finish Weight (lb.)	(+113F) 36 1 Frost
Physical MOL MOD Lens Finish	(+113F) 36 1 Frost
Physical MOL MOD Lens Finish Weight (lb.)	(+113F) 36 1 Frost
Physical MOL MOD Lens Finish Weight (lb.) Additional Information	(+113F) 36 1 Frost 0.34
Physical MOL MOD Lens Finish Weight (lb.) Additional Information Additional Info	(+113F) 36 1 Frost 0.34 Not for emergency lighting
Physical MOL MOD Lens Finish Weight (lb.) Additional Information Additional Info Tube Guard Use	(+113F) 36 1 Frost 0.34 Not for emergency lighting Approved for use with tube guards
Physical MOL MOD Lens Finish Weight (lb.) Additional Information Additional Info Tube Guard Use Warranty	(+113F) 36 1 Frost 0.34 Not for emergency lighting Approved for use with tube guards
Physical MOL MOD Lens Finish Weight (lb.) Additional Information Additional Info Tube Guard Use Warranty Compliance	(+113F) 36 1 Frost 0.34 Not for emergency lighting Approved for use with tube guards 5 Year Limited - T8 LED Bulbs
Physical MOL MOD Lens Finish Weight (lb.) Additional Information Additional Info Tube Guard Use Warranty Compliance Safety Listing	(+113F) 36 1 Frost 0.34 Not for emergency lighting Approved for use with tube guards 5 Year Limited - T8 LED Bulbs CULus Classified
Physical MOL MOD Lens Finish Weight (lb.) Additional Information Additional Info Tube Guard Use Warranty Compliance Safety Listing Location Rating	(+113F) 36 1 Frost 0.34 Not for emergency lighting Approved for use with tube guards 5 Year Limited - T8 LED Bulbs CULus Classified Damp
PhysicalMOLMODLens FinishWeight (lb.)Additional InformationAdditional InfoTube Guard UseWarrantyComplianceSafety ListingLocation RatingEnergy Star	(+113F) 36 1 Frost 0.34 Not for emergency lighting Approved for use with tube guards 5 Year Limited - T8 LED Bulbs CULus Classified Damp No
Physical MOL MOD Lens Finish Weight (lb.) Additional Information Additional Info Tube Guard Use Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved	(+113F) 36 1 Frost 0.34 Not for emergency lighting Approved for use with tube guards 5 Year Limited - T8 LED Bulbs CULus Classified Damp No Yes
Physical MOL MOD Lens Finish Weight (lb.) Additional Information Additional Info Tube Guard Use Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved DLC ID	(+113F) 36 1 Frost 0.34 Not for emergency lighting Approved for use with tube guards 5 Year Limited - T8 LED Bulbs CULus Classified Damp No Yes PLRWRJ8NB39P
Physical MOL MOD Lens Finish Weight (lb.) Additional Information Additional Info Tube Guard Use Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved DLC ID California Status	(+113F) 36 1 Frost 0.34 Not for emergency lighting Approved for use with tube guards 5 Year Limited - T8 LED Bulbs CULus Classified Damp No Yes PLRWRJ8NB39P Lawful for sale
Physical MOL MOD Lens Finish Weight (lb.) Additional Information Additional Info Tube Guard Use Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved DLC ID California Status RoHS Compliant	(+113F) 36 1 Frost 0.34 Not for emergency lighting Approved for use with tube guards 5 Year Limited - T8 LED Bulbs CULus Classified Damp No Yes PLRWRJ8NB39P Lawful for sale Yes

