

SA	T	CC	S <sup>2</sup>	11	9	44
$\mathbf{v}$		$\smile$	<i>,</i>		J	$\mathbf{T}$

23T5/LED/48-850/XD

Notes

General	
Status	Active
Watts	23W
Fluorescent Equivalent	54W
Ballast Type	Type C
Shape	T5
Base	Miniature Bi Pin
ANSI Base	G5
Nominal Length	48
Finish	Frost
CCT (Kelvin)	5000
Temperature	Natural Light
CRI	82
Lumens	3400L
Beam Spread	220
Dimmable	Yes-Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED
Electrical	
Ballasting Requirements	Ballast replaced with external driver
Operating Frequency	50/60 Hz
Power Factor	0.9
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)
Physical	
MOL	48
MOD	0.63
Lens Finish	Frost
Weight (lb.)	0.31
Additional Information	
Additional Info	Not for emergency lighting
Additional Info Warranty	Not for emergency lighting 5 Year Limited - 3 hr per day
Warranty	
Warranty	5 Year Limited - 3 hr per day
Warranty  Compliance  Safety Listing	5 Year Limited - 3 hr per day  cULus Classified
Warranty  Compliance  Safety Listing  Location Rating	5 Year Limited - 3 hr per day  cULus Classified  Damp
Warranty  Compliance  Safety Listing  Location Rating  Energy Star	5 Year Limited - 3 hr per day  cULus Classified  Damp  No
Warranty  Compliance  Safety Listing  Location Rating  Energy Star  DLC Approved	5 Year Limited - 3 hr per day  cULus Classified  Damp  No  Yes
Warranty  Compliance  Safety Listing  Location Rating  Energy Star  DLC Approved  DLC ID	5 Year Limited - 3 hr per day  cULus Classified  Damp  No  Yes  PLSYLZ6C510S
Warranty  Compliance  Safety Listing  Location Rating  Energy Star  DLC Approved  DLC ID  California Status	5 Year Limited - 3 hr per day  cULus Classified  Damp  No  Yes  PLSYLZ6C510S  Lawful for sale



NSF)





