

Project Name

Location

Prepared By



SATCO S11950

7T8/LED/18-830/BP

Notes

[www] 06-09-2021 01:41:21

General

Status	Active
Watts	7W
Incandescent Equivalent	75W
Fluorescent Equivalent	15W
Volts	120V-277V
Ballast Type	Type B
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	18.00
Finish	Frost
CCT (Kelvin)	3000
Temperature	Warm White
CRI	83
Lumens	700L
Beam Spread	160
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED

Electrical

Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60 Hz
Power Factor	0.9
THD	25%
Operating Temperature	-25C (-13F) to a maximum of +40C (+104F)

Physical

MOL	17.80
MOD	1.10
Material	Glass; Plastic
Lens Finish	Frost
Lens Material	Glass
Housing Color	White
Weight (lb.)	0.26

Additional Information

Shatter-Proof Type	PET Coated
Warranty	5 Year Limited - T8 LED Bulbs - Ballast Bypass

Compliance

Safety Listing	cULus Classified; cRUus
Location Rating	Damp
Energy Star	No
California Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	ETL Sanitation listed (conforms to NSF)

