

Project Name

Location

Prepared By



# SATCO S11955

30T8/LED/70-840/BP

**Notes**

[www] 06-09-2021 01:41:21

**General**

Status	Active
Watts	30W
Fluorescent Equivalent	70W
Volts	120V-277V
Ballast Type	Type B
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	70
Finish	Frost
CCT (Kelvin)	4000
Temperature	Cool White
CRI	83
Lumens	4000L
Beam Spread	160
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED

**Electrical**

Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60 Hz
Power Factor	0.9
THD	0.25
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)

**Physical**

MOL	70
MOD	1
Material	glass
Lens Finish	Frost
Lens Material	glass
Housing Color	White
Weight (lb.)	0.5

**Additional Information**

Shatter-Proof Type	PET Coated
Tube Guard Use	Yes
Warranty	5 Year Limited - T8 LED Bulbs - Ballast Bypass

**Compliance**

Safety Listing	cRUus; cULus Classified; ETL Listed
Location Rating	Damp
Energy Star	No
California Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes

