

Project Name

Location

Prepared By



SATCO S11964

18T8/LED/48-840/BP/R17D/HO

Notes

[www] 06-09-2021 01:41:21

General

Status	Active
Watts	18W
Fluorescent Equivalent	63W
Volts	120V-277V
Ballast Type	Type B
Shape	T8
Base	Recessed Double Contact HO/VHO
ANSI Base	R17d
Nominal Length	48
Finish	Frost
CCT (Kelvin)	4000
Temperature	Cool White
CRI	82
Lumens	2500L
Beam Spread	160
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED

Electrical

Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60 Hz
Power Factor	0.9
THD	25%
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)

Physical

MOL	46
MOD	1.1
Material	Glass
Lens Finish	Frost
Lens Material	Glass
Housing Color	White
Weight (lb.)	0.91

Additional Information

Shatter-Proof Type	Yes
Tube Guard Use	Yes
Warranty	5 Year Limited - T8 LED Bulbs - Ballast Bypass

Compliance

Safety Listing	cULus
Location Rating	Damp
Energy Star	No
California Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes

