

Project Name

Location

Prepared By



SATCO S11966

30T8/LED/72-840/BP/R17D/HO

Notes

[www] 06-09-2021 01:41:21

General

| | |
|------------------------|--------------------------------|
| Status | Active |
| Watts | 30W |
| Fluorescent Equivalent | 87W |
| Volts | 120V-277V |
| Ballast Type | Type B |
| Shape | T8 |
| Base | Recessed Double Contact HO/VHO |
| ANSI Base | R17d |
| Nominal Length | 72 |
| Finish | Frost |
| CCT (Kelvin) | 4000 |
| Temperature | Cool White |
| CRI | 82 |
| Lumens | 4200L |
| Beam Spread | 160 |
| Dimmable | Non-Dimmable |
| Hours Rated | 50000 |
| Lamp Type | Linear |
| Technology | LED |

Electrical

| | |
|-------------------------|---|
| Ballasting Requirements | Ballast Bypass |
| Operating Frequency | 50/60 Hz |
| Power Factor | 0.9 |
| THD | 25% |
| Operating Temperature | -20C (-4F) to a maximum of +45C (+113F) |

Physical

| | |
|---------------|-------|
| MOL | 70 |
| MOD | 1.1 |
| Material | Glass |
| Lens Finish | Frost |
| Lens Material | Glass |
| Housing Color | White |
| Weight (lb.) | 1.01 |

Additional Information

| | |
|--------------------|--|
| Shatter-Proof Type | Yes |
| Tube Guard Use | Yes |
| Warranty | 5 Year Limited - T8 LED Bulbs - Ballast Bypass |

Compliance

| | |
|-------------------|-----------------|
| Safety Listing | cULus |
| Location Rating | Damp |
| Energy Star | No |
| California Status | Lawful for sale |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| NSF Approved | Yes |

