

Project Name

Location

Prepared By



SATCO S11972

13T8U6/LED/22.5-840/DUAL

Notes

[www] 06-27-2021 00:19:11

General

Status	Active
Watts	13W
Fluorescent Equivalent	32W
Volts	120V-277V
Ballast Type	Type A/B
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	22.50
Finish	Frost
CCT (Kelvin)	4000
Temperature	Cool White
CRI	83
Lumens	2000L
Beam Spread	160
Dimmable	Yes-Dimmable
Hours Rated	50000
Lamp Type	U-Bend
Technology	LED

Electrical

Ballasting Requirements	Ballast required (Type A) or Ballast Bypass (Type B)
Operating Frequency	50/60 Hz
Power Factor	0.9
THD	25%
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)

Physical

MOL	22.50
MOD	1.1
Leg Spacing	6
Material	Plastic
Lens Finish	Frost
Lens Material	Plastic
Housing Color	White
Weight (lb.)	0.91

Additional Information

Shatter-Proof Type	Yes
Tube Guard Use	Yes
Warranty	5 Year Limited - T8 LED Bulbs

Compliance

Safety Listing	cULus Classified; cULus Listed
Location Rating	Damp
Energy Star	No
DLC Approved	Yes
DLC ID	PLX80LFIAOD6
California Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes

NSF Approved

Yes

Copyright 2020 Satco Products, Inc.
All Rights Reserved

For More Information Visit:
<http://www.satco.com/>

