Project Name

Location	Prepared By

SATCO S13145

120W/LED/HID/CCT/EX39/100-277V

Notes

General

Status	Active
Watts	120W
Incandescent Equivalent	750W
HID Equivalent	500W
Volts	100V-277V
Shape	Corncob
Base	Mogul Extended
ANSI Base	EX39
Finish	Clear
CCT (Kelvin)	3000K/4000K/5000K
Temperature	Warm to Cool White
CRI	80
Lumens	15600L-16800L
Beam Spread	360
Dimmable	Yes-Dimmable
Hours Rated	50000
Technology	LED
Min Compartment Size	Length: 9.85 in. Width: 9.85 in. Depth: 12.60 in.

Electrical

Operating Frequency	50/60 Hz
Dimming Note	Dimmable with optional modules; Dimming range from 100 to less than or equal to 20 percent depending on dimmer control
Power Factor	0.9
Burning Position	Up or Down Operation Only
Surge Protection	Built-in surge protection - 4KV
Operating Temperature	-30C (-22F) to a maximum of +45C (+113F)

Physical

MOL	11.61
MOD	5.16
Lens Finish	Clear
Lens Material	Polycarbonate (PC)
Housing Color	White/Grey
Photocell	Has Photocell
Weight (lb.)	3.48

Additional Information

Rated For Enclosed Fixture	Yes
IP Rating	IP64
Specification Note	This is not to be used with a ballast
Warranty	5 Year Limited - Hi-Pro

Compliance

Safety Listing	cULus - Classified; cULus - Certified; cULus - Listed
Location Rating	Damp
Energy Star	No
DLC Approved	Yes

DLC ID	PL48Y83ZQH0J; PLQPOPVP4M0
CA T20 / T24 Rationale	Exempt - Base Not Regulated
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

For More Information Visit:
http://www.satco.com/