SATCO NUVO

Project Name

Prepared By



Notes

General	
Status	Active
Watts	25W
Volts	100V-277V
Shape	AP23
Base	Medium
ANSI Base	E26
Finish	White
CCT (Kelvin)	3000K/4000K/5000K
Temperature	Warm to Cool White
CRI	80
Lumens	3000L/3375L/3250L
Beam Spread	290
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Туре А
Technology	LED
Min Compartment Size	Length: 6 in. Width: 6 in. Height: 8.5 in.
Electrical	
Operating Frequency	50/60 Hz
Operating Frequency Burning Position	50/60 Hz Base Up, Base Down, or Horizontal
	Base Up, Base Down, or
Burning Position	Base Up, Base Down, or Horizontal
Burning Position Surge Protection	Base Up, Base Down, or Horizontal
Burning Position Surge Protection Physical	Base Up, Base Down, or Horizontal Built-in surge protection - 1KV
Burning Position Surge Protection Physical MOL	Base Up, Base Down, or Horizontal Built-in surge protection - 1KV
Burning Position Surge Protection Physical MOL MOD Housing Color	Base Up, Base Down, or Horizontal Built-in surge protection - 1KV 5.12 2.83
Burning Position Surge Protection Physical MOL MOD Housing Color Additional Information	Base Up, Base Down, or Horizontal Built-in surge protection - 1KV 5.12 2.83 Gray
Burning Position Surge Protection Physical MOL MOD Housing Color	Base Up, Base Down, or Horizontal Built-in surge protection - 1KV 5.12 2.83 Gray
Burning Position Surge Protection Physical MOL MOD Housing Color Additional Information	Base Up, Base Down, or Horizontal Built-in surge protection - 1KV 5.12 2.83 Gray
Burning Position Surge Protection Physical MOL MOD Housing Color Additional Information Rated For Enclosed Fixture	Base Up, Base Down, or Horizontal Built-in surge protection - 1KV 5.12 2.83 Gray Yes Lumen/Watt/CCT Ratio Chart in
Burning Position Surge Protection Physical MOL MOD Housing Color Additional Information Rated For Enclosed Fixture Specification Note	Base Up, Base Down, or Horizontal Built-in surge protection - 1KV 5.12 2.83 Gray Yes Lumen/Watt/CCT Ratio Chart in Documents.
Burning Position Surge Protection Physical MOL MOD Housing Color Additional Information Rated For Enclosed Fixture Specification Note Warranty	Base Up, Base Down, or Horizontal Built-in surge protection - 1KV 5.12 2.83 Gray Yes Lumen/Watt/CCT Ratio Chart in Documents.
Burning Position Surge Protection Physical MOL MOD Housing Color Additional Information Rated For Enclosed Fixture Specification Note Warranty Compliance	Base Up, Base Down, or Horizontal Built-in surge protection - 1KV 5.12 2.83 Gray Yes Lumen/Watt/CCT Ratio Chart in Documents. 5 Year Limited
Burning Position Surge Protection Physical MOL MOD Housing Color Additional Information Rated For Enclosed Fixture Specification Note Warranty Compliance Safety Listing	Base Up, Base Down, or Horizontal Built-in surge protection - 1KV 5.12 2.83 Gray Yes Lumen/Watt/CCT Ratio Chart in Documents. 5 Year Limited
Burning Position Surge Protection Physical MOL MOD Housing Color Additional Information Rated For Enclosed Fixture Specification Note Warranty Compliance Safety Listing Location Rating	Base Up, Base Down, or Horizontal Built-in surge protection - 1KV 5.12 2.83 Gray Yes Lumen/Watt/CCT Ratio Chart in Documents. 5 Year Limited cULus Damp





