SATCO NUVO

Project Name

Prepared By



| M | | | - |
|----|---|----|---|
| IN | o | ΙЮ | ĸ |

| Status | Active |
|-------------------------|--------------------------------|
| Watts | 11W |
| Fluorescent Equivalent | 42W |
| Volts | 120V-277V |
| Ballast Type | Type B |
| Shape | T8 |
| Base | Recessed Double Contact HO/VHO |
| ANSI Base | R17d |
| Nominal Length | 30 |
| inish | Frost |
| CCT (Kelvin) | 6500 |
| Temperature | Daylight |
| CRI | 83 |
| umens | 1500L |
| Beam Spread | 360 |
| Dimmable | Non-Dimmable |
| Hours Rated | 50000 |
| _amp Type | Linear |
| Гесhnology | LED |
| Electrical | |
| Ballasting Requirements | Ballast Bypass |
| Operating Frequency | 50/60 Hz |
| Power Factor | 0.9 |

| Electrical | |
|-------------------------|--|
| Ballasting Requirements | Ballast Bypass |
| Operating Frequency | 50/60 Hz |
| Power Factor | 0.9 |
| Operating Temperature | -30C (-22F) to a maximum of +45C (+113F) |

| Physical | | |
|---------------|---------|--|
| MOL | 27.88 | |
| MOD | 1 | |
| Material | Plastic | |
| Lens Finish | Frost | |
| Lens Material | Nano | |
| Housing Color | White | |
| Weight (lb.) | 0.39 | |

| Additional Information | |
|------------------------|--|
| Tube Guard Use | Not Approved |
| Warranty | 5 Year Limited - T8 LED Bulbs - Ballast Bypass - Outdoor Sign |

| Compliance | |
|-------------------|------------------|
| Safety Listing | cULus Classified |
| Location Rating | Damp |
| Energy Star | No |
| California Status | Lawful for sale |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| NSF Approved | Yes |









All nights neserved http://www.satco.com/
