SATCO NUVO

Project Name

Location

Prepared By



Notes

www] 02-20-2023 02:53:1

General	
Status	Active
Substitute	S23165
Watts	45W
Incandescent Equivalent	300W
Fluorescent Equivalent	65W
HID Equivalent	175W
Volts	277V-347V
Shape	Corncob
Base	Mogul Extended
ANSI Base	EX39
Finish	Clear
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	80+
Lumens	6000L
Beam Spread	300
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Corncob
Technology	LED
	Length: 17.3 in. Width: 9.25 in.
Min Compartment Size	Depth: 9.25 in.
Ballasting Requirements	Ballast Bypass-Direct wire only 277-347V
Electrical	
Working Voltage	AC 250-380V
Working Voltage Operating Frequency	AC 250-380V 50-60Hz
Operating Frequency	50-60Hz
Operating Frequency Power Factor	50-60Hz >0.88
Operating Frequency Power Factor Burning Position	50-60Hz >0.88 Base Up or Down Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature
Operating Frequency Power Factor Burning Position Thermal Management Operating Temperature	50-60Hz >0.88 Base Up or Down Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I
Operating Frequency Power Factor Burning Position Thermal Management Operating Temperature Physical	50-60Hz >0.88 Base Up or Down Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -20C (-4F) to +65C (+149F)
Operating Frequency Power Factor Burning Position Thermal Management Operating Temperature Physical MOL	50-60Hz >0.88 Base Up or Down Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -20C (-4F) to +65C (+149F)
Operating Frequency Power Factor Burning Position Thermal Management Operating Temperature Physical MOL MOD	50-60Hz >0.88 Base Up or Down Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -20C (-4F) to +65C (+149F) 10.35 3.66
Operating Frequency Power Factor Burning Position Thermal Management Operating Temperature Physical MOL MOD Lens Finish	50-60Hz >0.88 Base Up or Down Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -20C (-4F) to +65C (+149F) 10.35 3.66 Clear
Operating Frequency Power Factor Burning Position Thermal Management Operating Temperature Physical MOL MOD Lens Finish Housing Color	50-60Hz >0.88 Base Up or Down Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -20C (-4F) to +65C (+149F) 10.35 3.66 Clear White/Grey
Operating Frequency Power Factor Burning Position Thermal Management Operating Temperature Physical MOL MOD Lens Finish	50-60Hz >0.88 Base Up or Down Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -20C (-4F) to +65C (+149F) 10.35 3.66 Clear
Operating Frequency Power Factor Burning Position Thermal Management Operating Temperature Physical MOL MOD Lens Finish Housing Color	50-60Hz >0.88 Base Up or Down Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -20C (-4F) to +65C (+149F) 10.35 3.66 Clear White/Grey
Operating Frequency Power Factor Burning Position Thermal Management Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.)	50-60Hz >0.88 Base Up or Down Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -20C (-4F) to +65C (+149F) 10.35 3.66 Clear White/Grey
Operating Frequency Power Factor Burning Position Thermal Management Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information	50-60Hz >0.88 Base Up or Down Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -20C (-4F) to +65C (+149F) 10.35 3.66 Clear White/Grey 2.15 Replaces HID, CFL, and Incandescent; UL approved for totally enclosed fixtures; Emits no
Operating Frequency Power Factor Burning Position Thermal Management Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information	50-60Hz >0.88 Base Up or Down Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -20C (-4F) to +65C (+149F) 10.35 3.66 Clear White/Grey 2.15 Replaces HID, CFL, and Incandescent; UL approved for totally enclosed fixtures; Emits no UV light / Contains no Mercury (Hg)
Operating Frequency Power Factor Burning Position Thermal Management Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info	50-60Hz >0.88 Base Up or Down Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -20C (-4F) to +65C (+149F) 10.35 3.66 Clear White/Grey 2.15 Replaces HID, CFL, and Incandescent; UL approved for totally enclosed fixtures; Emits no UV light / Contains no Mercury (Hg)
Operating Frequency Power Factor Burning Position Thermal Management Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating	50-60Hz >0.88 Base Up or Down Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -20C (-4F) to +65C (+149F) 10.35 3.66 Clear White/Grey 2.15 Replaces HID, CFL, and Incandescent; UL approved for totally enclosed fixtures; Emits no UV light / Contains no Mercury (Hg) Yes IP65
Operating Frequency Power Factor Burning Position Thermal Management Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Warranty	50-60Hz >0.88 Base Up or Down Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -20C (-4F) to +65C (+149F) 10.35 3.66 Clear White/Grey 2.15 Replaces HID, CFL, and Incandescent; UL approved for totally enclosed fixtures; Emits no UV light / Contains no Mercury (Hg) Yes IP65

Location Rating	Damp
Energy Star	No
DLC Approved	No
CA T20 / T24 Rationale	Exempt - Base Not Regulated
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Washington Status	Lawful for sale
Vermont Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

Copyright 2020 Satco Products, Inc. All Rights Reserved

For More Information Visit: http://www.satco.com/







