SATCO" NUVO"

Project Name

Location

Prepared By



SATCO S29798 40W/LED/HID/MB/2700K/100-277V

Notes

[www] 02-20-2023 02:53:18

General	
Status	Active
Substitute	S39798
Watts	40W
Incandescent Equivalent	300W
Fluorescent Equivalent	65W
HID Equivalent	175W
Volts	100V-277V
Shape	Corncob
Base	Mogul Extended
ANSI Base	EX39
Finish	Clear
CCT (Kelvin)	2700K
Temperature	Warm White
CRI	80+
Lumens	4880L
Beam Spread	360
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Corncob
Technology	LED
Min Compartment Size	Length: 8.27 in. Width: 9.25 in. Depth: 9.25 in.
Ballasting Requirements	Ballast Bypass
Electrical	
Operating Frequency	50/60Hz
Power Factor	>0.9
Burning Position	Base Up or Down
Burning Position Surge Protection	Base Up or Down Built-in surge protection - 1KV
Surge Protection	Built-in surge protection - 1KV
Surge Protection Operating Temperature	Built-in surge protection - 1KV
Surge Protection Operating Temperature Physical	Built-in surge protection - 1KV -20C (-4F) to +65C (+149F)
Surge Protection Operating Temperature Physical MOL	Built-in surge protection - 1KV -20C (-4F) to +65C (+149F) 7.88
Surge Protection Operating Temperature Physical MOL MOD	Built-in surge protection - 1KV -20C (-4F) to +65C (+149F) 7.88 3.5
Surge Protection Operating Temperature Physical MOL MOD Lens Finish	Built-in surge protection - 1KV -20C (-4F) to +65C (+149F) 7.88 3.5 Clear
Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color	Built-in surge protection - 1KV -20C (-4F) to +65C (+149F) 7.88 3.5 Clear White
Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.)	Built-in surge protection - 1KV -20C (-4F) to +65C (+149F) 7.88 3.5 Clear White 1.85 Width 360 deg 3.5 in.; Width 270
Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info	Built-in surge protection - 1KV -20C (-4F) to +65C (+149F) 7.88 3.5 Clear White 1.85 Width 360 deg 3.5 in.; Width 270 deg 7.7 in.; Width 180 deg 8.9 in.
Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture	Built-in surge protection - 1KV -20C (-4F) to +65C (+149F) 7.88 3.5 Clear White 1.85 Width 360 deg 3.5 in.; Width 270 deg 7.7 in.; Width 180 deg 8.9 in. Yes
Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info	Built-in surge protection - 1KV -20C (-4F) to +65C (+149F) 7.88 3.5 Clear White 1.85 Width 360 deg 3.5 in.; Width 270 deg 7.7 in.; Width 180 deg 8.9 in. Yes IP65
Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture	Built-in surge protection - 1KV -20C (-4F) to +65C (+149F) 7.88 3.5 Clear White 1.85 Width 360 deg 3.5 in.; Width 270 deg 7.7 in.; Width 180 deg 8.9 in. Yes
Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating	Built-in surge protection - 1KV -20C (-4F) to +65C (+149F) 7.88 3.5 Clear White 1.85 Width 360 deg 3.5 in.; Width 270 deg 7.7 in.; Width 180 deg 8.9 in. Yes IP65 Arms fully open diameter is 8.88
Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes	Built-in surge protection - 1KV-20C (-4F) to +65C (+149F)7.883.5ClearWhite1.85Width 360 deg 3.5 in.; Width 270deg 7.7 in.; Width 180 deg 8.9 in.YesIP65Arms fully open diameter is 8.88inches
Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty	Built-in surge protection - 1KV-20C (-4F) to +65C (+149F)7.883.5ClearWhite1.85Width 360 deg 3.5 in.; Width 270deg 7.7 in.; Width 180 deg 8.9 in.YesIP65Arms fully open diameter is 8.88inches
Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance	Built-in surge protection - 1KV-20C (-4F) to +65C (+149F)7.883.5ClearWhite1.85Width 360 deg 3.5 in.; Width 270 deg 7.7 in.; Width 180 deg 8.9 in.YesIP65Arms fully open diameter is 8.88 inches5 Year Limited - Hi-Pro
Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing	Built-in surge protection - 1KV-20C (-4F) to +65C (+149F)7.883.5ClearWhite1.85Width 360 deg 3.5 in.; Width 270deg 7.7 in.; Width 180 deg 8.9 in.YesIP65Arms fully open diameter is 8.88inches5 Year Limited - Hi-ProcULus - Listed
Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating	Built-in surge protection - 1KV -20C (-4F) to +65C (+149F) 7.88 3.5 Clear White 1.85 Width 360 deg 3.5 in.; Width 270 deg 7.7 in.; Width 180 deg 8.9 in. Yes IP65 Arms fully open diameter is 8.88 inches 5 Year Limited - Hi-Pro cULus - Listed Damp
Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating Energy Star	Built-in surge protection - 1KV-20C (-4F) to +65C (+149F)7.883.5ClearWhite1.85Width 360 deg 3.5 in.; Width 270 deg 7.7 in.; Width 180 deg 8.9 in.YesIP65Arms fully open diameter is 8.88 inches5 Year Limited - Hi-ProcULus - Listed Damp No

California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Washington Status	Lawful for sale
Vermont Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

Copyright 2020 Satco Products, Inc. All Rights Reserved

For More Information Visit: <u>http://www.satco.com/</u>

