SATCO NUVO

Project Name

Location

Prepared By



N	O	te	Ġ
		•	'n

ww] 02-20-2023 02:53:1

Shatter-Proof Type

Status	Discontinued
Substitute	S49395
Watts	80W
Incandescent Equivalent	400W
Fluorescent Equivalent	100W
HID Equivalent	320W
Volts	100V-277V
Shape	Corncob
Base	Mogul Extended
ANSI Base	EX39
Finish	Clear
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	80
Lumens	11440L
Beam Spread	300
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Corncob
Technology	LED
Min Compartment Size	Length: 9.25 in. Width: 17.32 in. Height: 9.25 in.
Ballasting Requirements	Ballast Bypass- Direct wire only 100V-277V
Electrical	
Working Voltage	AC 100-277V
Operating Frequency	50/60Hz
Operating Frequency Power Factor	50/60Hz >0.9
Power Factor	>0.9
Power Factor Burning Position	>0.9 Base Up or Down
Power Factor Burning Position Surge Protection	>0.9 Base Up or Down Built-in surge protection - 6KV Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature
Power Factor Burning Position Surge Protection Thermal Management	>0.9 Base Up or Down Built-in surge protection - 6KV Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I
Power Factor Burning Position Surge Protection Thermal Management Operating Temperature Physical	>0.9 Base Up or Down Built-in surge protection - 6KV Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -25C (-13F) to +45C (+113F)
Power Factor Burning Position Surge Protection Thermal Management Operating Temperature Physical MOL	>0.9 Base Up or Down Built-in surge protection - 6KV Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -25C (-13F) to +45C (+113F)
Power Factor Burning Position Surge Protection Thermal Management Operating Temperature Physical	>0.9 Base Up or Down Built-in surge protection - 6KV Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -25C (-13F) to +45C (+113F) 8.78 4.72
Power Factor Burning Position Surge Protection Thermal Management Operating Temperature Physical MOL MOD Lens Finish	>0.9 Base Up or Down Built-in surge protection - 6KV Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -25C (-13F) to +45C (+113F) 8.78 4.72 Clear
Power Factor Burning Position Surge Protection Thermal Management Operating Temperature Physical MOL MOD Lens Finish Lens Material	>0.9 Base Up or Down Built-in surge protection - 6KV Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -25C (-13F) to +45C (+113F) 8.78 4.72 Clear Plastic (PS)
Power Factor Burning Position Surge Protection Thermal Management Operating Temperature Physical MOL MOD Lens Finish	>0.9 Base Up or Down Built-in surge protection - 6KV Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -25C (-13F) to +45C (+113F) 8.78 4.72 Clear
Power Factor Burning Position Surge Protection Thermal Management Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.)	>0.9 Base Up or Down Built-in surge protection - 6KV Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -25C (-13F) to +45C (+113F) 8.78 4.72 Clear Plastic (PS) White
Power Factor Burning Position Surge Protection Thermal Management Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color	>0.9 Base Up or Down Built-in surge protection - 6KV Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -25C (-13F) to +45C (+113F) 8.78 4.72 Clear Plastic (PS) White 3.2
Power Factor Burning Position Surge Protection Thermal Management Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.)	>0.9 Base Up or Down Built-in surge protection - 6KV Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -25C (-13F) to +45C (+113F) 8.78 4.72 Clear Plastic (PS) White
Power Factor Burning Position Surge Protection Thermal Management Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	>0.9 Base Up or Down Built-in surge protection - 6KV Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -25C (-13F) to +45C (+113F) 8.78 4.72 Clear Plastic (PS) White 3.2 Emits no UV light; Contains no Mercury (Hg); Acceptable for use in
Power Factor Burning Position Surge Protection Thermal Management Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	>0.9 Base Up or Down Built-in surge protection - 6KV Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -25C (-13F) to +45C (+113F) 8.78 4.72 Clear Plastic (PS) White 3.2 Emits no UV light; Contains no Mercury (Hg); Acceptable for use in food prep areas
Power Factor Burning Position Surge Protection Thermal Management Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info	>0.9 Base Up or Down Built-in surge protection - 6KV Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -25C (-13F) to +45C (+113F) 8.78 4.72 Clear Plastic (PS) White 3.2 Emits no UV light; Contains no Mercury (Hg); Acceptable for use in food prep areas Yes

Shatter resistant materials

Warranty

5 Year Limited - Hi-Pro

Compliance		
Safety Listing	cULus - Listed	
Location Rating	Damp	
Energy Star	No	
DLC Approved	No	
CA T20 / T24 Rationale	Exempt - Base Not Regulated	
California Status	Lawful for sale in California	
Title 20 / 24 Status	Lawful for sale	
Colorado Status	Lawful for sale	
Hawaii Status	Lawful for sale	
Nevada Status	Lawful for sale	
Washington Status	Lawful for sale	
Vermont Status	Lawful for sale	
RoHS Compliant	Yes	
FCC Compliant	Yes	
SDS Sheet	LED_Lamp	

Copyright 2020 Satco Products, Inc. All Rights Reserved

For More Information Visit: http://www.satco.com/







