## SATCO NUVO

Project Name

Location

Prepared By



## **SATCO S39673**

45W/LED/HID/4K/100-277V EX39

Notes

www] 02-20-2023 02:53:

General	
Status	Discontinued
Substitute	S49673
Watts	45W
Incandescent Equivalent	300W
Fluorescent Equivalent	65W
HID Equivalent	175W
Volts	100V-277V
Shape	Corncob
Base	Mogul Extended
ANSI Base	EX39
Finish	Clear
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80
Lumens	6300L
Beam Spread	300
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Corncob
Technology	LED
	Length: 11 in. Width: 8 in. Depth:
Min Compartment Size	8 in.
Ballasting Requirements	Ballast Bypass- Direct wire only 100V-277V
Electrical	
Working Voltage	AC 100-277V
Working Voltage Operating Frequency	AC 100-277V 50/60Hz
Operating Frequency	50/60Hz
Operating Frequency Power Factor	50/60Hz >0.9
Operating Frequency Power Factor Burning Position	50/60Hz >0.9 Universal
Operating Frequency Power Factor Burning Position Surge Protection	50/60Hz >0.9 Universal Built-in surge protection - 4KV
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature	50/60Hz >0.9 Universal Built-in surge protection - 4KV
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical	50/60Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to +45C (+113F)
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL	50/60Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to +45C (+113F)  8.81
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD	50/60Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to +45C (+113F)  8.81 3.34
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish	50/60Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to +45C (+113F)  8.81 3.34 Clear
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material	50/60Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to +45C (+113F)  8.81 3.34 Clear Plastic (PS)
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature  Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color	50/60Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to +45C (+113F)  8.81 3.34 Clear Plastic (PS) White
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature  Physical  MOL  MOD  Lens Finish Lens Material Housing Color  Weight (lb.)	50/60Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to +45C (+113F)  8.81 3.34 Clear Plastic (PS) White
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	50/60Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to +45C (+113F)  8.81 3.34 Clear Plastic (PS) White 1.85  Emits no UV light; Contains no Mercury (Hg); Acceptable for use in
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature  Physical  MOL  MOD Lens Finish Lens Material Housing Color Weight (lb.)  Additional Information	50/60Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to +45C (+113F)  8.81 3.34 Clear Plastic (PS) White 1.85  Emits no UV light; Contains no Mercury (Hg); Acceptable for use in food prep areas
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature  Physical  MOL  MOD Lens Finish Lens Material Housing Color Weight (lb.)  Additional Information  Additional Info	50/60Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to +45C (+113F)  8.81 3.34 Clear Plastic (PS) White 1.85  Emits no UV light; Contains no Mercury (Hg); Acceptable for use in food prep areas Yes
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature  Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Additional Info	50/60Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to +45C (+113F)  8.81 3.34 Clear Plastic (PS) White 1.85  Emits no UV light; Contains no Mercury (Hg); Acceptable for use in food prep areas Yes IP64 DLC 5.1 replacement S23141;
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature  Physical  MOL  MOD Lens Finish Lens Material Housing Color Weight (lb.)  Additional Information  Additional Info  Rated For Enclosed Fixture IP Rating Specification Note	50/60Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to +45C (+113F)  8.81 3.34 Clear Plastic (PS) White 1.85  Emits no UV light; Contains no Mercury (Hg); Acceptable for use in food prep areas Yes IP64 DLC 5.1 replacement S23141; Non-DLC replacement S49673
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature  Physical  MOL  MOD Lens Finish Lens Material Housing Color Weight (lb.)  Additional Information  Additional Info  Rated For Enclosed Fixture IP Rating Specification Note  Shatter-Proof Type	50/60Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to +45C (+113F)  8.81 3.34 Clear Plastic (PS) White 1.85  Emits no UV light; Contains no Mercury (Hg); Acceptable for use in food prep areas Yes IP64 DLC 5.1 replacement S23141; Non-DLC replacement S49673 Shatter resistant materials
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature  Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Additional Info  Rated For Enclosed Fixture  IP Rating  Specification Note  Shatter-Proof Type  Warranty	50/60Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to +45C (+113F)  8.81 3.34 Clear Plastic (PS) White 1.85  Emits no UV light; Contains no Mercury (Hg); Acceptable for use in food prep areas Yes IP64 DLC 5.1 replacement S23141; Non-DLC replacement S49673 Shatter resistant materials

Location Rating	Damp
Energy Star	No
DLC Approved	No
CA T20 / T24 Rationale	Exempt - Base Not Regulated
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Washington Status	Lawful for sale
Vermont Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

Copyright 2020 Satco Products, Inc. All Rights Reserved

For More Information Visit: http://www.satco.com/







