## SATCO NUVO

Project Name

Location

Prepared By



N	o	te	S

ww] 02-20-2023 02:53:19

Shatter-Proof Type

General	
Status	Discontinued
Substitute	S49675
Watts	80W
Incandescent Equivalent	400W
Fluorescent Equivalent	100W
HID Equivalent	320W
Volts	100V-277V
Shape	Corncob
Base	Mogul Extended
ANSI Base	EX39
Finish	Clear
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80
Lumens	11200L
Beam Spread	300
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Corncob
Technology	LED
Min Compartment Size	Length: 17.32 in. Width: 9.25 in. Depth: 9.25 in.
Ballasting Requirements	Ballast Bypass- Direct wire only 100V-277V
Electrical	
	AC 100-277V
Working Voltage	AC 100-277V 50/60Hz
	50/60Hz
Working Voltage Operating Frequency Power Factor	50/60Hz >0.9
Working Voltage Operating Frequency Power Factor Burning Position	50/60Hz >0.9 Base Up or Down
Working Voltage Operating Frequency Power Factor	50/60Hz >0.9
Working Voltage Operating Frequency Power Factor Burning Position Surge Protection	50/60Hz >0.9  Base Up or Down  Built-in surge protection - 6KV  Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature
Working Voltage Operating Frequency Power Factor Burning Position Surge Protection Thermal Management	50/60Hz >0.9  Base Up or Down  Built-in surge protection - 6KV  Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I
Working Voltage  Operating Frequency  Power Factor  Burning Position  Surge Protection  Thermal Management  Operating Temperature	50/60Hz >0.9  Base Up or Down  Built-in surge protection - 6KV  Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I
Working Voltage Operating Frequency Power Factor Burning Position Surge Protection Thermal Management Operating Temperature Physical	50/60Hz >0.9  Base Up or Down  Built-in surge protection - 6KV  Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I  -25C (-13F) to +45C (+113F)
Working Voltage Operating Frequency Power Factor Burning Position Surge Protection Thermal Management Operating Temperature Physical MOL	50/60Hz >0.9  Base Up or Down  Built-in surge protection - 6KV  Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I  -25C (-13F) to +45C (+113F)
Working Voltage Operating Frequency Power Factor Burning Position Surge Protection  Thermal Management  Operating Temperature  Physical  MOL  MOD	50/60Hz >0.9  Base Up or Down  Built-in surge protection - 6KV  Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -25C (-13F) to +45C (+113F)  8.78 4.72
Working Voltage Operating Frequency Power Factor Burning Position Surge Protection  Thermal Management  Operating Temperature  Physical  MOL  MOD  Lens Finish	50/60Hz >0.9  Base Up or Down  Built-in surge protection - 6KV  Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -25C (-13F) to +45C (+113F)  8.78 4.72 Clear
Working Voltage Operating Frequency Power Factor Burning Position Surge Protection  Thermal Management  Operating Temperature  Physical  MOL  MOD  Lens Finish  Lens Material	50/60Hz >0.9  Base Up or Down  Built-in surge protection - 6KV  Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -25C (-13F) to +45C (+113F)  8.78 4.72 Clear Plastic (PS)
Working Voltage Operating Frequency Power Factor Burning Position Surge Protection  Thermal Management  Operating Temperature  Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color	50/60Hz >0.9  Base Up or Down  Built-in surge protection - 6KV  Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -25C (-13F) to +45C (+113F)  8.78 4.72 Clear Plastic (PS) White
Working Voltage Operating Frequency Power Factor Burning Position Surge Protection  Thermal Management  Operating Temperature  Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color  Weight (lb.)	50/60Hz >0.9  Base Up or Down  Built-in surge protection - 6KV  Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -25C (-13F) to +45C (+113F)  8.78 4.72 Clear Plastic (PS) White
Working Voltage Operating Frequency Power Factor Burning Position Surge Protection  Thermal Management  Operating Temperature  Physical  MOL  MOD  Lens Finish  Lens Material Housing Color  Weight (lb.)  Additional Information	50/60Hz >0.9  Base Up or Down  Built-in surge protection - 6KV  Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -25C (-13F) to +45C (+113F)  8.78 4.72 Clear Plastic (PS) White 3.2  Emits no UV light; Contains no Mercury (Hg); Acceptable for use in
Working Voltage Operating Frequency Power Factor Burning Position Surge Protection  Thermal Management Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.)  Additional Information	50/60Hz  >0.9  Base Up or Down  Built-in surge protection - 6KV  Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I  -25C (-13F) to +45C (+113F)  8.78  4.72  Clear  Plastic (PS)  White  3.2  Emits no UV light; Contains no Mercury (Hg); Acceptable for use in food prep areas

Non-DLC replacement S49675

Shatter resistant materials

Warranty

5 Year Limited - Hi-Pro

Compliance		
Safety Listing	cULus - Listed	
Location Rating	Damp	
Energy Star	No	
DLC Approved	No	
CA T20 / T24 Rationale	Exempt - Base Not Regulated	
California Status	Lawful for sale in California	
Title 20 / 24 Status	Lawful for sale	
Colorado Status	Lawful for sale	
Hawaii Status	Lawful for sale	
Nevada Status	Lawful for sale	
Washington Status	Lawful for sale	
Vermont Status	Lawful for sale	
RoHS Compliant	Yes	
FCC Compliant	Yes	
SDS Sheet	LED_Lamp	

Copyright 2020 Satco Products, Inc. All Rights Reserved

For More Information Visit: <a href="http://www.satco.com/">http://www.satco.com/</a>







