## SATCO NUVO

General

Project Name

Location

Prepared By



100W/LED/HID/4K/100-277V/EX39

## Notes

Shatter-Proof Type

General	
Status	Discontinued
Substitute	S49676
Watts	100W
Incandescent Equivalent	500W
Fluorescent Equivalent	150W
HID Equivalent	400W
Volts	100V-277V
Shape	Corncob
Base	Mogul Extended
ANSI Base	EX39
Finish	Clear
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80
Lumens	14000L
Beam Spread	300
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Corncob
Technology	LED
Min Compartment Size	Length: 17.32 in. Width: 9.25 in. Depth: 9.25 in.
Ballasting Requirements	Ballast Bypass- Direct wire only 100V-277V
Electrical	
Working Voltage	AC 100-277V
Working Voltage Operating Frequency	AC 100-277V 50/60Hz
Operating Frequency	50/60Hz
Operating Frequency Power Factor	50/60Hz >0.9
Operating Frequency Power Factor Burning Position	50/60Hz >0.9 Base Up or Down
Operating Frequency Power Factor Burning Position Surge Protection	50/60Hz >0.9  Base Up or Down  Built-in surge protection - 6KV  Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature
Operating Frequency Power Factor Burning Position Surge Protection  Thermal Management  Operating Temperature	50/60Hz >0.9  Base Up or Down  Built-in surge protection - 6KV  Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I
Operating Frequency Power Factor Burning Position Surge Protection Thermal Management	50/60Hz >0.9  Base Up or Down  Built-in surge protection - 6KV  Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I
Operating Frequency Power Factor Burning Position Surge Protection  Thermal Management  Operating Temperature	50/60Hz >0.9  Base Up or Down  Built-in surge protection - 6KV  Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I
Operating Frequency Power Factor Burning Position Surge Protection  Thermal Management  Operating Temperature  Physical	50/60Hz >0.9  Base Up or Down  Built-in surge protection - 6KV  Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I  -25C (-13F) to +45C (+113F)
Operating Frequency Power Factor Burning Position Surge Protection  Thermal Management  Operating Temperature  Physical  MOL	50/60Hz >0.9  Base Up or Down  Built-in surge protection - 6KV  Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -25C (-13F) to +45C (+113F)  9.88 4.72 Clear
Operating Frequency Power Factor Burning Position Surge Protection  Thermal Management  Operating Temperature  Physical  MOL  MOD	50/60Hz >0.9  Base Up or Down  Built-in surge protection - 6KV  Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -25C (-13F) to +45C (+113F)  9.88 4.72
Operating Frequency Power Factor Burning Position Surge Protection  Thermal Management  Operating Temperature  Physical  MOL  MOD  Lens Finish	50/60Hz >0.9  Base Up or Down  Built-in surge protection - 6KV  Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -25C (-13F) to +45C (+113F)  9.88 4.72 Clear
Operating Frequency Power Factor Burning Position Surge Protection  Thermal Management  Operating Temperature  Physical  MOL  MOD  Lens Finish  Lens Material	50/60Hz >0.9  Base Up or Down  Built-in surge protection - 6KV  Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I  -25C (-13F) to +45C (+113F)  9.88 4.72 Clear Plastic (PS)
Operating Frequency Power Factor Burning Position Surge Protection  Thermal Management  Operating Temperature  Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color	50/60Hz >0.9  Base Up or Down  Built-in surge protection - 6KV  Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -25C (-13F) to +45C (+113F)  9.88 4.72 Clear Plastic (PS)  White
Operating Frequency Power Factor Burning Position Surge Protection  Thermal Management  Operating Temperature  Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color  Weight (lb.)	50/60Hz >0.9  Base Up or Down  Built-in surge protection - 6KV  Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -25C (-13F) to +45C (+113F)  9.88 4.72 Clear Plastic (PS)  White
Operating Frequency Power Factor Burning Position Surge Protection  Thermal Management  Operating Temperature  Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information	50/60Hz >0.9  Base Up or Down  Built-in surge protection - 6KV  Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -25C (-13F) to +45C (+113F)  9.88 4.72 Clear Plastic (PS) White 3.45  Emits no UV light; Contains no Mercury (Hg); Acceptable for use in
Operating Frequency Power Factor Burning Position Surge Protection  Thermal Management  Operating Temperature  Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information	50/60Hz  >0.9  Base Up or Down  Built-in surge protection - 6KV  Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I  -25C (-13F) to +45C (+113F)  9.88  4.72  Clear  Plastic (PS)  White  3.45  Emits no UV light; Contains no Mercury (Hg); Acceptable for use in food prep areas
Operating Frequency Power Factor Burning Position Surge Protection  Thermal Management  Operating Temperature  Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Additional Info	50/60Hz >0.9  Base Up or Down  Built-in surge protection - 6KV  Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -25C (-13F) to +45C (+113F)  9.88 4.72 Clear Plastic (PS) White 3.45  Emits no UV light; Contains no Mercury (Hg); Acceptable for use in food prep areas Yes

Shatter resistant materials

Warranty

5 Year Limited - Hi-Pro

Compliance	
Safety Listing	cULus - Listed
Location Rating	Damp
Energy Star	No
DLC Approved	No
CA T20 / T24 Rationale	Exempt - Base Not Regulated
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Washington Status	Lawful for sale
Vermont Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

Copyright 2020 Satco Products, Inc. All Rights Reserved

For More Information Visit: <a href="http://www.satco.com/">http://www.satco.com/</a>







