

Project Name

Location

Prepared By



SATCO S8536

9WPLV/LED/830/BP/2P

Notes

[www] 06-09-2021 01:41:24

General

Status	Active
Watts	9W
Fluorescent Equivalent	See Notes
Volts	120V-277V
Ballast Type	Type B
Shape	PL
Base	2-Pin
ANSI Base	G24d
Finish	Frost
CCT (Kelvin)	3000
Temperature	Warm White
CRI	82
Lumens	950L
Beam Spread	120
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	PL
Burning Position	Vertical Operation
Technology	LED

Electrical

Ballasting Requirements	Ballast Bypass-Direct wire only 100-277V
Operating Frequency	50/60 Hz
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)

Physical

MOL	4.69
MOD	1.91

Additional Information

Additional Info	In G24d (2-pin) sockets replaces 18 and 26 watt CFLs; In G24q (4-pin) sockets replaces 13; 18; and 26 watt CFLs
Installation Notes	2-pin LED lamps work in both 2-pin (magnetic) and 4-pin (electronic) sockets.
Warranty	5 Year Limited - 10 hr per day

Compliance

Safety Listing	cULus Classified
Location Rating	Damp
Energy Star	No
California Status	Lawful for sale
RoHS Compliant	Yes
SDS Sheet	LED_Lamp