

Project Name

Location Prepared By



SATCO S8891

13T8/LED/48-835/DUAL/BP-DR

Notes

[www] 10-11-2021 02:06:

General	
Status	Active
Watts	13W
Volts	120V-277V
Ballast Type	Type A/B
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48.00
Finish	Frost
CCT (Kelvin)	3500
Temperature	Neutral White
CRI	83
Lumens	1800L
Beam Spread	240
Dimmable	Yes-Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED
Electrical	
Ballasting Requirements	Ballast required (Type A) or Ballas Bypass (Type B)
Operating Frequency	50/60 Hz
Power Factor	0.96
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)
Physical	
MOL	47.78
MOD	1
Material	Glass
Lens Finish	Frost
Housing Color	White
Additional Information	
Additional Info	Do not use with dimmers in by- pass mode. Check the ballast for dimming capability when using with

Additional Information	
Additional Info	Do not use with dimmers in by- pass mode. Check the ballast for dimming capability when using with a ballast.
Shatter-Proof Type	PET Coated
Specification Note	Ballast Compatible - bare lamp is 12W; Ballast Bypass - 13W.; Protection from arcing- Power must be turned off prior to installing lamps. Sockets must be in good working order, not broken, cracked or electrically compromised. If arcing occurs at the lamp pin, thermal fuse may activate to avoid overheating of lamp.
Warranty	5 Year Limited - T8 LED Bulbs
Compliance	
Safety Listing	cULus Listed for Type A; cULus Classified for Type B
Location Rating	Damp

Energy Star	No
DLC Approved	Yes
DLC ID	PLGF1IVR6PF5
California Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes

Copyright 2020 Satco Products, Inc. All Rights Reserved

For More Information Visit: http://www.satco.com/







