

ASB

DUAL ENERGY DUCT HEATER



AUTONOMY + SAVINGS = DUAL ENERGY DUCT HEATER

The Stelpro duct heater is designed to guarantee maximum operational safety while ensuring comfort and economy. It is offered in two sizes and combined with a deflector kit for better performance and increased versatility. Please contact your local contractor for details on how to save with the Residential Rate DT.

TEMPERATURE SENSOR

FOR A CONSTANT TEMPERATURE AND OVERHEATING DETECTION

INTERLOCK DEVICE

PREVENTS THE SIMULTANEOUS START-UP OF TWO HEATING SOURCES

DEFLECTOR KIT

PERMITS TO ADAPT TO AN EXISTING SYSTEM

USER-FRIENDLY CONTROLS

COLOR

- charcoal

FINISH

- galvanized steel

MANUFACTURING

- robust monopiece galvanized steel cabinet
- pilot lights that clearly identify the selected modes
- deflector kit (included)
- plenum temperature sensor (abnormal condition detection)
- diagnostic pilot lights
- each element is protected by a set of thermal cut-outs (manual and automatic)

HEATING ASSEMBLY AREA

- 16 in. x 18 in.
- 19 in. x 19 in.

ELEMENTS

- modulating elements for increased comfort and separately framed allowing for quick and easy replacement

CONTROL

- mode selector
- auto transfer function

INSTALLATION

- upflow position

WARRANTY

- three years

°STELPRO

Stelpro reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. Returns are not accepted for orders of products with optional colors. For all the latest models and prices, please refer to our website at www.stelpro.com.



FC_SB_US_260722

TECHNICAL SPECIFICATIONS

PRODUCT	POWER & VOLTAGE		AMPERAGE	HEATING ASSEMBLY AREA	HEIGHT OA	WIDTH OA	DEPTH OA
	KW	VOLTS	AMPERES	IN.	IN.	IN.	IN.
ASB05211	5/3.8	240/208	20.8/18.1	16 X 18	12 9/16	20 1/8	20 9/16 - 23 9/16
ASB05212	5/3.8	240/208	20.8/18.1	19 X 19	12 9/16	20 1/8	20 9/16 - 23 9/16
ASB10211	10/7.5	240/208	41.7/36.1	16 X 18	12 9/16	20 1/8	20 9/16 - 23 9/16
ASB10212	10/7.5	240/208	41.7/36.1	19 X 19	12 9/16	20 1/8	20 9/16 - 23 9/16
ASB15211	15/11.3	240/208	62.5/54.2	16 X 18	12 9/16	20 1/8	20 9/16 - 23 9/16
ASB15212	15/11.3	240/208	62.5/54.2	19 X 19	12 9/16	20 1/8	20 9/16 - 23 9/16
ASB18211	18/13.5	240/208	75/65	16 X 18	12 9/16	20 1/8	20 9/16 - 23 9/16
ASB18212	18/13.5	240/208	75/65	19 X 19	12 9/16	20 1/8	20 9/16 - 23 9/16
ASB20211	20/15	240/208	83.3/72.2	16 X 18	12 9/16	20 1/8	20 9/16 - 23 9/16
ASB20212	20/15	240/208	83.3/72.2	19 X 19	12 9/16	20 1/8	20 9/16 - 23 9/16
ASB23211	23/17.3	240/208	95.8/83.1	16 X 18	12 9/16	20 1/8	20 9/16 - 23 9/16
ASB23212	23/17.3	240/208	95.8/83.1	19 X 19	12 9/16	20 1/8	20 9/16 - 23 9/16
ASB27211	27/20.3	240/208	112.5/97.5	16 X 18	12 9/16	20 1/8	20 9/16 - 23 9/16
ASB27212	27/20.3	240/208	112.5/97.5	19 X 19	12 9/16	20 1/8	20 9/16 - 23 9/16
ASB30211	30/22.5	240/208	125/108.3	16 X 18	12 9/16	20 1/8	20 9/16 - 23 9/16
ASB30212	30/22.5	240/208	125/108.3	19 X 19	12 9/16	20 1/8	20 9/16 - 23 9/16

MODE ADJUSTMENTS

**BIÉNERGIE
DUAL ENERGY**

- ÉLECTRIQUE/ELECTRIC
- COMBUSTIBLE/FOSSIL FUEL
- THERMOSTAT

**COMBUSTIBLE
FOSSIL FUEL**

- MARCHE/ON

**ÉLECTRIQUE
ELECTRIC**

- MARCHE/ON

DUAL ENERGY MODE	FOSSIL FUEL MODE	ELECTRIC MODE
heating mode changes automatically depending on the temperature outside	only fossil fuel is used	only the duct heater is used

INSTALLATION

