

ASSO | SONOMA™

WALL FAN HEATER

TEMPORARILY UNAVAILABLE



SONOMA™



THE NEW STANDARD IN FAN HEATERS

The Sonoma fan heater is the new standard for those who need a quiet but fast heating solution. With the same footprint as most popular models, the Sonoma offers easy one-screw cover installation. Its impact-resistant facade makes it a safe and sustainable choice. Ideal for your bathroom, the integrated timer provides the warmth you want right when you need it most. Designed with the user experience in mind, the Sonoma fan heater provides optimal comfort to any room.

QUICK AND EASY INSTALLATION

EASILY RETROFITS MOST POPULAR MODELS

VERY QUIET FAN HEATER

CAN BE INSTALLED IN A CHILD'S BEDROOM

DESIGNED WITH THE USER EXPERIENCE IN MIND

CONTROLS LOCATED AT THE TOP OF THE UNIT

OPTIMAL SAFETY

INTEGRATED THERMAL CUTOFF
IMPACT-RESISTANT FACADE

FAST COMFORT

RAPID TEMPERATURE RISE

COLOR

- white

FINISH

- epoxy-polyester powdercoat

MANUFACTURING

- 22-gauge steel cabinet and 20-gauge steel grille
- thermal protection with manual reset
- additional thermal protection with a thermal fuse (must be replaced if triggered)

ELEMENT

- nichrome element produces instant heat

CONTROL

- built-in thermostat (optional)
- built-in timer (optional)
- wall thermostat (not included) – the use of an electronic thermostat is strongly recommended

INSTALLATION

- recessed
- wall mounted with surface adapter (optional)

WARRANTY

- five years

IDEAL FOR:

bedroom, living room, kitchen, hallway, lobby, office, bathroom (model with timer and thermostat)

ACCESSORIES

PRODUCT	DESCRIPTION
ASSOBB6	back box (6)
ASSOT1W	built-in single pole thermostat [120 V-347 V]
ASSOT2W	built-in double pole thermostat [120V-347V]
ASSOSAW	surface adapter (white)

°STELPRO

Stelpro reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. No returns accepted on optional-color products. For all the latest models and prices, please refer to our website at www.stelpro.com.



FC_ASSO_US_170822



TECHNICAL SPECIFICATIONS

WITHOUT THERMOSTAT	BUILT-IN THERMOSTAT	BUILT-IN THERMOSTAT AND TIMER	VOLTAGE	POWER*		HEIGHT	LENGTH	WEIGHT
CODE	CODE	CODE	VOLTS	WATTS	BTU/H	IN.	IN.	LB
ASSO1001WCW	ASSO1001T2W	ASSO1001T2TW	120	1000 or 500	3413 or 1706	12 3/8	9 1/16	7.4
ASSO1008WCW	ASSO1008T2W	ASSO1008T2TW	208	1000 or 500	3413 or 1706	12 3/8	9 1/16	7.4
ASSO1002WCW	ASSO1002T2W	ASSO1002T2TW	240/208	1000/750 or 500/375	3413/2560 or 1706/1280	12 3/8	9 1/16	7.4

Add WBB for unit without back box (available for U.S. market only).

*Choice of power at installation

TECHNICAL DRAWINGS

