

SHC CONVECTOR



EFFICIENT HEATING

Our SHC convector has pleasing rounded sides and beautiful modern lines. It is available with or without an ultra-accurate built-in electronic thermostat, so you can choose the level of control you want. This attractive unit is available in two colours and many voltages making it suitable for both commercial and residential applications. A real gem!

EXCELLENT VALUE

TOTALLY QUIET

BUILT-IN ELECTRONIC THERMOSTAT (OPTIONAL) WITH A BACKLIT SCREEN

ADAPTS TO MULTIPLE MARKETS

AVAILABLE IN: 120 V, 208 V, 240 V,
347 V AND 600 V



**BUILT-IN ELECTRONIC THERMOSTAT AVAILABLE
FOR THE 120 V TO 240 V MODELS**



ALSO AVAILABLE
EASY INSTALLATION WITH 120 V PLUG

IDEAL FOR:

kitchen, living room, bedroom, office, basement,
commercial space

COLOURS

- **standard:** white, soft white
- **Orora (optional):** refer to www.stelpro.com/en-CA/Orora

FINISH

- epoxy-polyester powdercoat

MANUFACTURING

- 22-gauge steel cabinet and 20-gauge steel front
- the cabinet height improves the chimney effect
- bottom air intake and front air discharge
- 6 ft (2 m) 16 gage molded cable with 3-prong grounded, 120 V plug (SHC1501P model)

ELEMENTS

- two stainless steel tubular sheathed elements insulated with nylon sleeves to reduce expansion and contraction noises

CONTROL

- electronic thermostat required: built-in electronic thermostat with LCD screen (optional) or electronic wall thermostat (not included)

INSTALLATION

- surface mounted only
- wall mounted at least 4 in. from the floor
- concealed mounting bracket (included)
- back entry plate with cable clamps (included)

WARRANTY

- five years, *three years on electronic components

°STELPRO

Stelpro reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. **No returns accepted on optional-colour products.**
For all the latest models and prices, please refer to our website at www.stelpro.com.



TECHNICAL SPECIFICATIONS

BUILT-IN THERMOSTAT CODE	PRICE	WITHOUT THERMOSTAT CODE	PRICE	POWER WATTS	VOLTAGE VOLTS	HEIGHT		LENGTH		WEIGHT	
						MM	IN.	MM	IN.	KG	LB
SHC0501	270.00	SHC0501WC	218.00	500	120	446	17 9/16	440	17 5/16	5.1	11.2
SHC0508	270.00	SHC0508WC	218.00	500	208	446	17 9/16	440	17 5/16	5.1	11.2
SHC0502	231.00	SHC0502WC	180.00	500/375	240/208	446	17 9/16	440	17 5/16	5.1	11.2
---	---	SHC0503WC	286.00	500	347	446	17 9/16	440	17 5/16	5.1	11.2
SHC1001	286.00	SHC1001WC	235.00	1000	120	446	17 9/16	581	22 7/8	6.0	13.3
SHC1008	286.00	SHC1008WC	235.00	1000	208	446	17 9/16	581	22 7/8	6.0	13.3
SHC1002	247.00	SHC1002WC	195.00	1000/750	240/208	446	17 9/16	581	22 7/8	6.0	13.3
---	---	SHC1003WC	302.00	1000	347	446	17 9/16	581	22 7/8	6.0	13.3
---	---	SHC1006WC	302.00	1000	600	446	17 9/16	581	22 7/8	6.0	13.3
SHC1501	300.00	SHC1501WC	248.00	1500	120	446	17 9/16	727	28 5/8	7.1	15.7
SHC1508	300.00	SHC1508WC	248.00	1500	208	446	17 9/16	727	28 5/8	7.1	15.7
SHC1502	261.00	SHC1502WC	209.00	1500/1125	240/208	446	17 9/16	727	28 5/8	7.1	15.7
---	---	SHC1503WC	316.00	1500	347	446	17 9/16	727	28 5/8	7.1	15.7
---	---	SHC1506WC	316.00	1500	600	446	17 9/16	727	28 5/8	7.1	15.7
SHC2008	326.00	SHC2008WC	274.00	2000	208	446	17 9/16	889	35	8.6	18.9
SHC2002	288.00	SHC2002WC	236.00	2000/1500	240/208	446	17 9/16	889	35	8.6	18.9
---	---	SHC2003WC	343.00	2000	347	446	17 9/16	889	35	8.6	18.9
---	---	SHC2006WC	343.00	2000	600	446	17 9/16	889	35	8.6	18.9
MODEL WITH 120 V PLUG (RESIDENTIAL OUTLET)											
SHC1501P*	324.00	---	---	1500	120	446	17 9/16	727	28 5/8	7.1	15.7

Add W for white or SW for soft white (consult the optional colours chart or contact your Stelpro representative for all other colours).
 Mechanical wall thermostats are not compatible with the without thermostat model (WC). An electronic thermostat is required. Models also available in 277 V and 480 V.
 * Available in white only
 --- not available

ACCESSORIES

PRODUCT	DESCRIPTION	PRICE
SHCRE153*	built-in electronic low voltage relay [15 A @ 120 V-347 V]	77.00
SHCRE156*	built-in electronic low voltage relay [6 A @ 600 V]	125.00
SHCRE153T*	built-in electronic low voltage relay c/w transformer 24 V [15 A @ 208 V-347 V]	96.00

Electronic relays can receive a PWM (pulsed width modulation) or digital (on/off) signal.
 * Factory installed

TECHNICAL DRAWINGS

