

CEILING FAN HEATER

SK SERIES

HEATED FROM ABOVE, SOOTHING BELOW

The AIR CURTAIN™ ceiling fan heater silently beams down heat from above. This unique model is ideal for rooms where wall space is limited. In bathrooms, the AIR CURTAIN™ can be installed just outside the shower or bathtub. With its ceiling-recessed casing, the AIR CURTAIN™ is an excellent way to provide discreet air circulation. The result: uniform heating and air movement, and reduction in mirror and window fog. By adding a wall timer, you can use it on demand.



CEILING MOUNTED

IDEAL FOR ROOMS WITH LIMITED WALL SPACE

HEATING ON DEMAND

WALL TIMER (OPTIONAL)

COMPACT AND QUIET

347 V MODEL AVAILABLE

IDEAL FOR:

BATHROOM, ENTRYWAY, DAY CARE CENTRE, ROOM WITH LIMITED WALL SPACE

COLOURS

- standard: white, soft white
- ORORA (optional): denim blue, midnight blue, turquoise, moss green, canary yellow, red, orange, anodized aluminum paint, gravel gray, charcoal, espresso, black (refer to page 8 of the catalogue)

FINISH

epoxy-polyester powdercoat

MANUFACTURING

- 22-gauge steel cabinet and 20-gauge steel grille
- 1/4 in. (6.4 mm) deep front grille
- easy access for maintenance purposes (no screws)

THERMAL PROTECTION

thermal protection with automatic reset

ELEMENT

nichrome element produces instant heat

CONTROL

- built-in thermostat (optional)
- wall thermostat (not included) – the use of an electronic thermostat is strongly recommended
- 60-minute timer (optional)

INSTALLATION

- ceiling mounted (recommended height of 8 ft., maximum of 9 ft.)
- surface mounted with surface adapter (optional)
- recessed or surface mounted with adapter for suspended ceiling (optional)
- unit can be mounted parallel or perpendicular to ceiling beams
- approved to be recessed in mineral wool; for all other materials please verify with the manufacturer of the insulating product

ACCESSORIES

PRODUCT	DESCRIPTION	PRICE
SKT1*	tamper-proof built-in thermostat [120 V-347 V] (grille must be removed to access this type of thermostat)	60.75
SKTBA*	adapter for suspended ceiling (2 ft. x 2 ft.) - recessed or surface mounted with surface adapter (not included)	84.75
SKSA*	surface adapter (SK model)	78.25
FD60MCW70	60-minute wall timer [120 V-277 V]	58.25

* Add W for white or SW for soft white

* Factory installed

TECHNICAL SPECIFICATIONS

WITHOUT CONTROL		BUILT-IN THERMOSTAT		24 V CONTROL		POWER	VOLTAGE	PHASE	FLOW	THROW DISTANCE		HEAT RISE		WEIGHT	
CODE	PRICE	CODE	PRICE	CODE	PRICE	WATTS	VOLTS	NB	CFM	M	FT.	°C	°F	KG	LB
SK0501	217.00	---	---	---	---	500	120	1	60	2.4	8	26	46	5	11
SK0508	217.00	---	---	---	---	500	208	1	60	2.4	8	26	46	5	11
SK0502	217.00	---	---	---	---	500/375	240/208	1	60	2.4	8	26	46	5	11
SK0507	313.00	---	---	---	---	500	277	1	60	2.4	8	26	46	5	11
SK0503	313.00	SK0503T	374.00	SK0503C24	313.00	500	347	1	60	2.4	8	26	46	5	11
SK0751	217.00	---	---	---	---	750	120	1	60	2.4	8	42	75	5	11
SK0758	217.00	---	---	---	---	750	208	1	60	2.4	8	42	75	5	11
SK0752	217.00	---	---	---	---	750/560	240/208	1	60	2.4	8	42	75	5	11
SK0757	313.00	---	---	---	---	750	277	1	60	2.4	8	42	75	5	11
SK0753	313.00	SK0753T	374.00	SK0753C24	313.00	750	347	1	60	2.4	8	42	75	5	11
SK1001	229.00	---	---	---	---	1000	120	1	60	2.4	8	54	97	5	11
SK1008	229.00	---	---	---	---	1000	208	1	60	2.4	8	54	97	5	11
SK1002	229.00	---	---	---	---	1000/750	240/208	1	60	2.4	8	54	97	5	11
SK1007	325.00	---	---	---	---	1000	277	1	60	2.4	8	54	97	5	11
SK1003	325.00	SK1003T	386.00	SK1003C24	325.00	1000	347	1	60	2.4	8	54	97	5	11
SK1251	241.00	---	---	---	---	1250	120	1	60	2.4	8	79	143	5	11
SK1258	241.00	---	---	---	---	1250	208	1	60	2.4	8	79	143	5	11
SK1252	241.00	---	---	---	---	1250/940	240/208	1	60	2.4	8	79	143	5	11
SK1257	338.00	---	---	---	---	1250	277	1	60	2.4	8	79	143	5	11
SK1253	338.00	SK1253T	398.00	SK1253C24	338.00	1250	347	1	60	2.4	8	79	143	5	11
SK1501	254.00	---	---	---	---	1500	120	1	60	2.4	8	102	184	5	11
SK1508	254.00	---	---	---	---	1500	208	1	60	2.4	8	102	184	5	11
SK1502	254.00	---	---	---	---	1500/1125	240/208	1	60	2.4	8	102	184	5	11
SK1507	349.00	---	---	---	---	1500	277	1	60	2.4	8	102	184	5	11
SK1503	349.00	SK1503T	410.00	SK1503C24	349.00	1500	347	1	60	2.4	8	102	184	5	11
---	---	---	---	---	---	2000	120	1	90	3.2	10'6"	109	196	5	11
---	---	---	---	---	---	2000	208	1	90	3.2	10'6"	109	196	5	11
SK2002	289.00	---	---	---	---	2000/1500	240/208	1	90	3.2	10'6"	109	196	5	11
SK2007	386.00	---	---	---	---	2000	277	1	90	3.2	10'6"	109	196	5	11
SK2003	386.00	SK2003T	447.00	SK2003C24	386.00	2000	347	1	90	3.2	10'6"	109	196	5	11

Add W for white or SW for soft white (see page 8 of the catalogue for optional colours and contact your *STELPRO representative for all other colours)
 --- not available

TECHNICAL DRAWINGS

