SYLVANIA Lamps

ULTRA LED™ High Lumen Filament Lamp

Application

SYLVANIA High Lumen Filament lamps offer a reliable light source with high efficacy and long life. With up to 153 lumens per watt (LPW) initial efficacy and excellent lumen maintenance, these lamps deliver consistent light levels throughout their long lifetime. Offered in a traditional and familiar ED28 shape with both clear and frosted coatings, they are ideal in retrofitting existing HID fixtures.

Benefits and Features

- Easy to install, these lamps are UL type B and run on direct voltage bypassing old ballasts
- Offered in clear and frosted versions, these lamps leverage the efficacy of LEDs with the traditional filament style
- Unlike traditional technologies, these LED replacements are not bound to single operating positions
- Up to 153 LPW
- 5000K color temperature
- CRI >80
- Offered in 26 watts
- 300° distribution
- Energy savings up to 76%
- Made of glass for high quality light distribution

Electrical

- 120-277Vac
- Power Factor >90%
- THD <20%
- Phase-Cut dimmable
- 6kV surge protection

Rated Life

- 25,000 hours (L₇₀)

Warranty

- 5-year
- NLB Trusted Warranty Program

Ambient Operating Range

- -40°F to +140°F (-40°C to +60°C)



Wattage Comparison

Traditional Source	Traditional System Wattage	LED System Wattage	Energy Savings	Energy Savings Over Lamp Life*
HID Metal Halide	100W	26W	73%	\$401
HID Metal Halide	150W	26W	76%	\$627

^{*}Energy savings over life of lamp calculated at \$0.11/kWh

Certifications and Listings

- cULus

Lead Free

RoHS

- Mercury Free

- FCC

Installation

- Requires an easy ballast-bypass and runs on 120-277V
- Suitable for both open and enclosed fixtures

Additional Specifications

CEC Exempt















Specification Data

Catalog #	Туре
Project	
Comments	
Prepared by	

Ordering Guide

LED	26	HIDR	1	XX	8	50	1	MED
LED Lamps	Wattage	Lamp Type		Finish	CRI	Color Temperature		Base Type
and Retrofits	26 = 26 Watts	HID Replacement		CL = Clear	8 = > 80	50 = 5000K		MED = Medium Base
				FR = Frosted				

Ordering Information


			Input				Color		Total		
Item	Ordering	Power	Voltage				Temperature		Fixture		Operating
Number	Abbreviation	(W)	(V)	Finish	Dimming	CRI	(CCT)	Distribution	Lumens	LPW	Position
41356	LED26HIDR/CL850/MED	26	120-277	Clear	Phase-Cut	>80	5000K	Omnidirectional	4000lm	153	Any
41746	LED26HIDR/FR850/MED	26	120-277	Frosted	Phase-Cut	> 80	5000K	Omnidirectional	4000lm	153	Any

Compatible Dimmers

Manufacturer	Model	
Leviton SureSlide	6674	
Lutron Caseta	PD-6WCL	
Lutron Diva	DVCL-153P	
Lutron Diva	DVELV-300P	
Lutron Maestro C-L	MACL-153M	
Lutron Maestro	MAELV-600	

Physical Information

	(A) Length (mm)	(B) Diameter (mm)	
LED26HIDR	225	90	_



LEDVANCE LLC
200 Ballardvale Street
Wilmington, MA 01887 USA
Phone 1-800-LIGHTBULB (1-800-544-4828)
www.ledvanceUS.com

SYLVANIA and LEDVANCE are registered trademarks.

All other trademarks are those of their respective owners.

Licensee of product trademark SYLVANIA in general lighting.

Specifications subject to change without notice.





