

SYLVANIA Luminaires

UltraLED™ CCT Selectable Canopy

Application

The Canopy luminaires are environmentally preferable LED alternatives to traditional HID luminaires, offering up to 79% in energy savings. Ideal in place of traditional luminaires, or as new installations, the Canopy series is offered in four wattages/lumen packages for illuminating parking garages, covered exterior corridors or walkways and stairwells.

Benefits and Features

- Slim, lightweight design
- High efficacy meets DLC requirements and increases rebate opportunities
- CCT selectability increases luminaire versatility
- Up to 135 LPW
- 3000K, 4000K or 5000K CCT Selectable
- CRI >80
- Offered in 20, 40, 60, and 75 watts
- Two color options: bronze or white
- Garage and Canopy optics
- Energy savings up to 79%

Electrical

- 120-277V_{AC}
- Power factor >90%
- THD <20%
- 0-10V dimmable

Rated Life

- 100,000 hours (L₇₀)

Warranty

- 5-year

Ambient Operating Range

- -30°F to +122°F (-22°C to +50°C)

Item #
Type
Project
Notes
Date



Wattage Comparison

Traditional Source	Traditional System Wattage	LED System Wattage	Energy Savings
35W HPS	42	20	52%
50W HPS	62	20	68%
70W HPS	91	20	78%
70W HPS	91	40	56%
100W HPS	120	40	67%
100W MH	130	40	69%
150W HPS	170	40	76%
150W MH	188	40	79%
150W HPS	170	60	65%
150W MH	188	60	68%
175W MH	210	60	71%
250W MH	290	60	79%

Certifications and Listings

- cULus rated for wet locations
- RoHS
- IP65
- FCC
- DLC

Installation

- Luminaire mounts to recessed outlet box or can be pendant mounted (accessories not included).



Ordering Guide

CANOPYS	4X	/ XX	UNV	D	8	SC2	/ X5	/ BZ	/ X
Product Name	Generation	Wattage	Voltage	Dimming	CRI	Color Temp	Distribution	Color/Finish	Options
CANOPYS = UltraLED™	4A = 20 or 40W versions	20 = 20 watts 40 = 40 watts	UNV = 120-277V	D = 0-10V	8 = >80	SC2 = selectable 3000, 4000 or 5000K CCT	G5 = Garage Optics C5 = Canopy Optics	BZ = Bronze WH = White	Blank = no option D = Motion/Daylight Sensor M = Motion Sensor P = Photocontrol
CCT Selectable Canopy Luminaire	4B = 60 or 75W versions	60 = 60 watts 75 = 75 watts							


Ordering Information

Item Number	Ordering Abbreviation	Power (W)	Input Voltage (V)	Dimming	CRI	Color Temp	Distribution	Total Fixture Lumens	LPW*	DLC	Options	Finish
62223	CANOPYS4A/020UNVD8SC2/C5/BZ	20	120-277	0-10V	80	3000, 4000 or 5000K	Canopy	2500	125	Premium	-	Bronze
61312	CANOPYS4A/020UNVD8SC2/C5/WH	20	120-277	0-10V	80	3000, 4000 or 5000K	Canopy	2500	125	Premium	-	White
62224	CANOPYS4A/020UNVD8SC2/G5/BZ	20	120-277	0-10V	80	3000, 4000 or 5000K	Garage	2500	125	Premium	-	Bronze
62225	CANOPYS4A/020UNVD8SC2/G5/BZ/D	20	120-277	0-10V	80	3000, 4000 or 5000K	Garage	2500	125	Premium	Motion/Daylight Sensor	Bronze
62226	CANOPYS4A/040UNVD8SC2/C5/BZ	40	120-277	0-10V	80	3000, 4000 or 5000K	Canopy	5000	125	Premium	-	Bronze
61313	CANOPYS4A/040UNVD8SC2/C5/WH	40	120-277	0-10V	80	3000, 4000 or 5000K	Canopy	5000	125	Premium	-	White
62227	CANOPYS4A/040UNVD8SC2/G5/BZ	40	120-277	0-10V	80	3000, 4000 or 5000K	Garage	5000	125	Premium	-	Bronze
62228	CANOPYS4A/040UNVD8SC2/G5/BZ/D	40	120-277	0-10V	80	3000, 4000 or 5000K	Garage	5000	125	Premium	Motion/Daylight Sensor	Bronze
62229	CANOPYS4B/060UNVD8SC2/C5/BZ	60	120-277	0-10V	80	3000, 4000 or 5000K	Canopy	7500	125	Premium	-	Bronze
61314	CANOPYS4B/060UNVD8SC2/C5/WH	60	120-277	0-10V	80	3000, 4000 or 5000K	Canopy	7500	125	Premium	-	White
62230	CANOPYS4B/060UNVD8SC2/G5/BZ	60	120-277	0-10V	80	3000, 4000 or 5000K	Garage	7500	125	Premium	-	Bronze
62231	CANOPYS4B/060UNVD8SC2/G5/BZ/D	60	120-277	0-10V	80	3000, 4000 or 5000K	Garage	7500	125	Premium	Motion/Daylight Sensor	Bronze
61309	CANOPYS4B/075UNVD8SC2/C5/BZ	75	120-277	0-10V	80	3000, 4000 or 5000K	Canopy	9375	125	Premium	-	Bronze
61315	CANOPYS4B/075UNVD8SC2/C5/WH	75	120-277	0-10V	80	3000, 4000 or 5000K	Canopy	9375	125	Premium	-	White
61310	CANOPYS4B/075UNVD8SC2/G5/BZ	75	120-277	0-10V	80	3000, 4000 or 5000K	Garage	9375	125	Premium	-	Bronze
61311	CANOPYS4B/075UNVD8SC2/G5/BZ/D	75	120-277	0-10V	80	3000, 4000 or 5000K	Garage	9375	125	Premium	Motion/Daylight Sensor	Bronze

*LPW is calculated at 3000K

Physical Information

Lamp Description	(A) Length (in)	(B) Width (in)	(C) Height (in)
UltraLED Canopy 20 and 40W versions	7.992	7.992	3.661
UltraLED Canopy 60 and 75W versions	10	10	4.173



Accessories

Item Number	Ordering Abbreviation	Distribution
60683	CANOPY3A/MTGPLATE/12/BZ	12.5" Mounting Plate, Bronze
60684	CANOPY3A/MTGPLATE/16/BZ	16" Mounting Plate, Bronze

LEDVANCE LLC
 200 Ballardvale Street
 Wilmington, MA 01887 USA
 Phone 1-800-LIGHTBULB (1-800-544-4828)
 www.sylvania.com

Name: _____
 Email: _____
 Phone: _____

SYLVANIA and LEDVANCE are registered trademarks.
 All other trademarks are those of their respective owners.
 Licensee of product trademark SYLVANIA in general lighting.
 Specifications subject to change without notice.

[/sylvania](https://www.facebook.com/sylvania) [/sylvania](https://www.instagram.com/sylvania)

