SYLVANIA Luminaires

ValueLED™ CCT Selectable Small Wall Pack

Application

The ValueLED Small Wall Pack luminaires are environmentally preferable LED alternatives to traditional HID luminaires, offering up to 68% in energy savings. Ideal in place of traditional luminaires, or as new installations, the Small Wall Pack series is offered in several wattages/lumen packages for illuminating building exteriors, outdoor corridors, walkways, and stairwells.

Benefits and Features

- CCT Selectable (3000K, 4000K, or 5000K) enabled through switch located inside fixture
- IP65 and IK08 rated body with aluminum backplate and polycarbonate lens offers easy mounting, reducing installation and maintenance costs
- DLC listing ensure energy efficiency and provide uniform and even lighting
- Photosensor included provides additional energy savings
- Up to 120 LPW
- Offered in 15 watts
- Non-cutoff distribution
- Energy savings up to 68%

Electrical

- 120-277Vac
- Power Factor > 0.9
- THD < 20%

Rated Life

150,000 hours (L₇₀)

Warranty

- 5-year
- NLB Trusted Warranty Program

Operating Temperature

-40°F to +104°F (-40°C to +40°C)

Item #			
Туре			
Project			
Notes			
Date			



Wattage Comparison

Traditional Source	Traditional System Wattage	LED System Wattage	Energy Savings
50W HPS	62	15	68%
50W MH	62	15	68%

Certifications and Listings

- cULus - DLC RoHS - IK08
- IP65 - TAA Compliant
- FCC

Installation

Luminaire mounts to exterior wall. Level included in back plate.
















Ordering Guide

SMWLPAK	N2A	/	015	UNV	D	8	SC2	/	BZ	/	Р
Product Name	Generation/Distribution		Wattage	Voltage	Dimming	CRI	Color Temp		Color/Finish		Options
SMWLPAK =	N2A = Generation 2A, non-cutoff		015 = 15 Watts	120-277V	D = 0-10V	CRI = >80	SC2 = 3000, 4000		BZ = Bronze Finish		P = Photocell
Small Wall Pack							or 5000K				

Ordering Information

Item		Power	Input			Color		Total Fixture			
Number	Ordering Abbreviation	(W)	Voltage (V)	Dimming	CRI	Temp.	Distribution	Lumens	LPW	Options	DLC
61750	SMWLPAKN2A/015UNVD8SC2/BZ/P	15	120-277	0-10V	>80	3000, 4000 or	Non-cutoff	1800	120	Photocell	Standard
						5000K					

Physical Information



LEDVANCE LLC 200 Ballardvale Street Wilmington, MA 01887 USA Phone 1-800-LIGHTBULB (1-800-544-4828) www.ledvanceUS.com

SYLVANIA and LEDVANCE are registered trademarks.

All other trademarks are those of their respective owners.

Licensee of product trademark SYLVANIA in general lighting.

Specifications subject to change without notice.







