

LED Smooth Face Snap-In CCT Selectable Downlights

Product Specifications

TCP's LED Smooth Face Snap-In CCT Selectable Downlights are the perfect choice for remodeling or new construction projects. The slim, energy-efficient design is easy to install and offers a rated lifetime of 50,000 hours.

Reasons to choose the LED Smooth Face Snap-In CCT Selectable Downlights from TCP

- 4" and 6" diameter sizes
- Direct wire no recessed can required
- Easy installation
- Slim, low-profile design
- Excellent color consistency
- Dimmable

- Highly efficient LEDs and driver
- Back-lit technology
- 50,000 hours rated life
- UL approved for damp locations
- IC rated
- Energy Star® Certified

Hospitality

Drop ceilings

Remodeling

Ideal Applications

- New construction
- Residential
- Office
- Retail









LED Smooth Face Snap-In CCT Selectable Downlights

Applications

Slim, low-profile design and easy snap-in installation make these downlights ideal for $4^{\prime\prime}$ and $6^{\prime\prime}$ new construction applications.

Construction

- Integrated junction box for direct wire application
- Spring loaded tabs for easy installation

Electrical

- UL approved for damp locations
- Easily access wiring for quick installation
- 50,000 hour rated life

Optics

- Excellent color consistency and CRI
- Smooth, uniform dimming
- Highly efficient LEDs and driver
- Triac dimming

Accessories

• 4"/6" Adjustable Frame Kit is also available: 461NFRAMEKIT



Listings

cULus Listed, RoHS and Energy Star® Certified

Warranty

Five year limited warranty against defects in manufacturing.



LED Smooth Face Snap-In CCT Selectabe Downlights

ITEM #	DESCRIPTION	VOLTAGE	INCAND. WATTS	WATTAGE	LUMENS	LPW	COLOR	CRI	BEAM ANGLE	MOL (IN)	DIAMETER (IN)
DR4BLSFCCT1	4" SMOOTH FACE SNAP-IN 27K/30K/35K	120	75	10	850	85	27K/30K/35K	80	90°	3	5
DR4BLSFCCT2	4" SMOOTH FACE SNAP-IN 30K/40K/50K	120	75	10	850	85	30K/40K/50K	80	90°	3	5
DR6BLSFCCT1	6" SMOOTH FACE SNAP-IN 27K/30K/35K	120	85	14	1100	78.6	27K/30K/35K	80	100°	3	7.125
DR6BLSFCCT2	6" SMOOTH FACE SNAP-IN 30K/40K/50K	120	85	14	1100	78.6	30K/40K/50K	80	100°	3	7.125













TCP Standard LED Lamps, LED Filament Lamps and TCP Downlights have been tested to work with the following dimmers:

BRAND	MODEL
LUTRON	AYCL-153P
	CTCL-153PD-H
	CTCL-53PD-H
	DV-600P
	DV-600PR-WH
	DV-603PH-WH
	DVCL-153P
	LGCL-153P
	MACL_153M
	MSCL-OP153M
	PD-6WCL
	SCL-153PR
	SELV-300P
	TGCL-153P
	MRF2S-6ELV120-WH
LEVITON	6811
	6602
	6631
	6672
	6672-L
	6674
	DSL06
	IPLO6
COOPER	DALO6P
	SALO6P

*Dimming compatibility tests are performed under a controlled lab environment. Field conditions may vary from this type of environment. Dimmers may differ by age and versions under the same item number which may affect compatibility. Compatibility may also extend beyond this list as TCP products should work with most C-L Type Triac Dimmers. TCP recommends trying a few dimmer-lamp combinations in an onsite test to ensure compatibility and performance before a major installation. If there's a dimmer not on this list we can perform a lab test for compatibility.











TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 20 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:	Catalog Number:
Date:	Туре:
Model:	Notes:
Project:	TCD
Rep:	we know light."

For more information on the quality and care TCP can deliver, call us at 800.324.1496 or visit tcpi.com