



# Pro Line Family of LED Lamps

## Product Specifications



For an affordable LED upgrade, switch to TCP's Pro Line LED Lamps. Pro Line LEDs are available in both SMD and Filament technology, across a full range of lamp shapes, from A-Lamps, to BR30 and PAR38 lamps. See how you can maximize savings and minimize maintenance costs with Pro Line LED Lamps.

### Reasons to choose the Pro Line LED Lamps from TCP

- Long-life: 15,000 hours minimizes replacement and maintenance costs
- Inexpensive alternative for cost-sensitive projects
- ANSI Construction Compliant to fit most general applications
- Dimmable
- UL approved for damp location means lamps can be used outdoors when protected from the elements

### Ideal Applications

- Commercial
- Retail
- Industrial
- Residential

### Specifications

|                           |              |               |          |
|---------------------------|--------------|---------------|----------|
| Input Line Voltage .....  | 120 VAC      | CRI.....      | 80       |
| Input Line Frequency..... | 50/60HZ      | Base.....     | E26, E12 |
| Lamp Life (Rated) .....   | 15,000 hours | Warranty..... | 3 Years  |
| Dimmable.....             | Yes          |               |          |



## Specifications



A19 40W  
E26 Base



A19 60W  
E26 Base



A19 75W  
E26 Base



A19 100W  
E26 Base

| ITEM #  | ITEM DESCRIPTION                   | WATTS | INCAN WATTS | CRI | LUMENS | LPW   | COLOR TEMP | CASE QTY |
|---|------------------------------------|-------|-------------|-----|--------|-------|------------|----------|
| <b>A19 • Dimmable • 15,000 Hours • E26 Base</b> |                                    |       |             |     |        |       |            |          |
| FPA19D40E26CL27K                                | Pro Line Filament 40W A19 27K CLR  | 4.5   | 40          | 80  | 450    | 100   | 2700K      | 12       |
| FPA19D40E26CL30K                                | Pro Line Filament 40W A19 30K CLR  | 4.5   | 40          | 80  | 450    | 100   | 3000K      | 12       |
| FPA19D40E26CL41K                                | Pro Line Filament 40W A19 41K CLR  | 4.5   | 40          | 80  | 450    | 100   | 4100K      | 12       |
| FPA19D40E26CL50K                                | Pro Line Filament 40W A19 50K CLR  | 4.5   | 40          | 80  | 450    | 100   | 5000K      | 12       |
| FPA19D60E26CL27K                                | Pro Line Filament 60W A19 27K CLR  | 7     | 60          | 80  | 800    | 114.2 | 2700K      | 12       |
| FPA19D60E26CL30K                                | Pro Line Filament 60W A19 30K CLR  | 7     | 60          | 80  | 800    | 114.2 | 3000K      | 12       |
| FPA19D60E26CL41K                                | Pro Line Filament 60W A19 41K CLR  | 7     | 60          | 80  | 800    | 114.2 | 4100K      | 12       |
| FPA19D60E26CL50K                                | Pro Line Filament 60W A19 50K CLR  | 7     | 60          | 80  | 800    | 114.2 | 5000K      | 12       |
| FPA19D75E26CL27K                                | Pro Line Filament 75W A19 27K CLR  | 10.5  | 75          | 80  | 1100   | 104.7 | 2700K      | 12       |
| FPA19D75E26CL30K                                | Pro Line Filament 75W A19 30K CLR  | 10.5  | 75          | 80  | 1100   | 104.7 | 3000K      | 12       |
| FPA19D75E26CL41K                                | Pro Line Filament 75W A19 41K CLR  | 10.5  | 75          | 80  | 1100   | 104.7 | 4100K      | 12       |
| FPA19D75E26CL50K                                | Pro Line Filament 75W A19 50K CLR  | 10.5  | 75          | 80  | 1100   | 104.7 | 5000K      | 12       |
| FPA19D100E26CL27K                               | Pro Line Filament 100W A19 27K CLR | 14.5  | 100         | 80  | 1600   | 110.3 | 2700K      | 6        |
| FPA19D100E26CL30K                               | Pro Line Filament 100W A19 30K CLR | 14.5  | 100         | 80  | 1600   | 110.3 | 3000K      | 6        |
| FPA19D100E26CL41K                               | Pro Line Filament 100W A19 41K CLR | 14.5  | 100         | 80  | 1600   | 110.3 | 4100K      | 6        |
| FPA19D100E26CL50K                               | Pro Line Filament 100W A19 50K CLR | 14.5  | 100         | 80  | 1600   | 110.3 | 5000K      | 6        |

## Specifications



| ITEM #  | DESCRIPTION                     | WATTS | INCAND. WATTS | CRI | LUMENS | LPW   | COLOR | FINISH | HOURS  | MOL (inches) | DIA (inches) | BASE | WARRANTY YEARS | CASE QTY |
|---|---------------------------------|-------|---------------|-----|--------|-------|-------|--------|--------|--------------|--------------|------|----------------|----------|
| <b>LED All Glass A-LAMP • 15,000 Hour</b>                               |                                 |       |               |     |        |       |       |        |        |              |              |      |                |          |
| <b>4.5W A19 • Dimmable</b>  |                                 |       |               |     |        |       |       |        |        |              |              |      |                |          |
| LFF40A19D1527K  | LED 40W EQ GLASS A19 DIM 27K FR | 4.5   | 40            | 80  | 425    | 94.4  | 2700K | FROST  | 15,000 | 4.2          | 2.4          | E26  | 3              | 12       |
| LFC40A19D1527K  | LED 40W EQ GLASS A19 DIM 27K CL | 4.5   | 40            | 80  | 425    | 94.4  | 2700K | CLEAR  | 15,000 | 4.2          | 2.4          | E26  | 3              | 12       |
| <b>8W A19 • Dimmable</b>  |                                 |       |               |     |        |       |       |        |        |              |              |      |                |          |
| LFF60A19D1550K  | LED 60W EQ GLASS A19 DIM 50K    | 8     | 60            | 80  | 725    | 90.6  | 5000K | FROST  | 15,000 | 4.2          | 2.4          | E26  | 3              | 12       |
| <b>8W A19 • Non-Dimmable</b>  |                                 |       |               |     |        |       |       |        |        |              |              |      |                |          |
| LFC60A19N1527K  | LED 60W EQ GLASS A19 ND 27K CL  | 8     | 60            | 80  | 725    | 90.6  | 2700K | CLEAR  | 15,000 | 4.2          | 2.4          | E26  | 3              | 12       |
| LFC60A19N1550K  | LED 60W EQ GLASS A19 ND 50K CL  | 8     | 60            | 80  | 725    | 90.6  | 5000K | CLEAR  | 15,000 | 4.2          | 2.4          | E26  | 3              | 12       |
| <b>LED All Glass Decorative 40W Equivalent • Dimmable • 15,000 Hour</b> |                                 |       |               |     |        |       |       |        |        |              |              |      |                |          |
| FG25D40V27W   | LED 4W G25 DIM 27K FR PRO LINE  | 4     | 40            | 80  | 350    | 87.5  | 2700K | FROST  | 15,000 | 4.5          | 3.2          | E26  | 3              | 12       |
| <b>LED A-LAMP • 15,000 Hour</b>   |                                 |       |               |     |        |       |       |        |        |              |              |      |                |          |
| <b>14W A19 • Non-Dimmable</b>   |                                 |       |               |     |        |       |       |        |        |              |              |      |                |          |
| L100A19N15V27K  | LED 14W A19 ND 27K PRO LINE     | 14    | 100           | 80  | 1500   | 107.1 | 2700K | FROST  | 15,000 | 4.5          | 2.6          | E26  | 3              | 12       |
| <b>LED BR • Dimmable • 15,000 Hour</b>                                  |                                 |       |               |     |        |       |       |        |        |              |              |      |                |          |
| L50R20D15V27K   | LED 7W R20 DIM 27K PRO LINE     | 7.5   | 50            | 80  | 500    | 66.7  | 2700K | FROST  | 15,000 | 3.8          | 2.5          | E26  | 3              | 12       |
| L65BR30D15V27K  | LED 9W BR30 DIM 27K PRO LINE    | 9     | 65            | 80  | 665    | 73.9  | 2700K | FROST  | 15,000 | 4.8          | 3.7          | E26  | 3              | 12       |
| L75BR40D15V27K  | LED 14W BR40 DIM 27K PRO LINE   | 14    | 75            | 80  | 1065   | 76.1  | 2700K | FROST  | 15,000 | 5.6          | 7.3          | E26  | 3              | 12       |
| <b>LED PAR* • Dimmable • 15,000 Hour</b>                                |                                 |       |               |     |        |       |       |        |        |              |              |      |                |          |
| L50P20D15V30KFL   | LED 7W P20 DIM 30K FL PRO LINE  | 7     | 50            | 80  | 525    | 75    | 3000K | FROST  | 15,000 | 3.4          | 2.3          | E26  | 3              | 12       |
| L75P30D15V30KFL   | LED 10W P30 DIM 30K FL PRO LINE | 9     | 75            | 80  | 720    | 80    | 3000K | FROST  | 15,000 | 4.8          | 3.9          | E26  | 3              | 12       |
| L90P38D15V30KFL   | LED 13W P38 DIM 30K FL PRO LINE | 13    | 90            | 80  | 1100   | 84.6  | 3000K | FROST  | 15,000 | 5.3          | 4.8          | E26  | 3              | 12       |

\* ALL PAR LAMPS HAVE A 40° BEAM ANGLE AND ARE SUITABLE FOR WET LOCATIONS.

| SUGGESTED DIMMER COMPATIBILITY |                |
|--------------------------------|----------------|
| MANUFACTURER                   | MODEL NUMBER   |
| Leviton                        | R50-IPLO6-10M  |
|                                | R61-06674-POI  |
| Lutron                         | CTCL-153PDH-WH |
|                                | TGCL-153PH-WH  |
|                                | DVVCL-153PH-WH |

Note: E26 compatible dimmer

# TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 30 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:

Date:

Model:

Project:

Rep:

Catalog Number:

Type:

Notes:



For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit [tcp.com](http://tcp.com)

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516