



LED Universal Voltage 120-277V Lamps

Product Specifications



TCP's LED Universal Voltage 120-277V Lamps are now available in A-lamps, BR30s, and PAR38s.

Reasons to choose LED Universal Voltage 120-277V Lamps from TCP

- Long life: 25,000 hours minimizes replacement and maintenance costs
- Uses up to 85% less energy than halogen alternatives
- Excellent color consistency and CRI
- PAR38 lamps are UL approved for wet locations
- Highly durable plastic

Ideal Applications

- Commercial
- Industrial
- Docks
- Warehouses
- Work sites
- Outdoor flood

Specifications

Input Line Voltage 120-277 VAC
 Input Line Frequency..... 50/60Hz
 Lamp Life (Rated) 25,000 hours
 Minimum Starting Temp -22°F/-30°C

Maximum Operating Temp..... 113°F/45°C
 CRI..... 80
 Warranty 5 years





LED Universal Voltage 120-277V Lamps

Specifications

| ITEM # | DESCRIPTION | ENERGY STAR | CBCP | WATTS | LIFE | REPLACEMENT | LUMENS | BEAM ANGLE | CCT | CRI | MOL (inches) | DIA (inches) | BASE | MASTER PACK |
|----------------------------------------------------------------|-------------------------------|-------------|------|-------|-------|-------------|--------|------------|-------|-----|--------------|--------------|------|-------------|
| 23W LED A23 Non Dimmable* • Includes E26 to E39 Adapter | | | | | | | | | | | | | | |
| L200A23N25UNV27K | LED A23 200W ND 27K 120-277 | NO | - | 24 | 25000 | 200 | 3000 | OMNI | 2700K | 80 | 6.3 | 3.3 | E26 | 12 |
| L200A23N25UNV30K | LED A23 200W ND 30K 120-277 | NO | - | 24 | 25000 | 200 | 3000 | OMNI | 3000K | 80 | 6.3 | 3.3 | E26 | 12 |
| L200A23N25UNV41K | LED A23 200W ND 41K 120-277 | NO | - | 24 | 25000 | 200 | 3000 | OMNI | 4100K | 80 | 6.3 | 3.3 | E26 | 12 |
| L200A23N25UNV50K | LED A23 200W ND 50K 120-277 | NO | - | 24 | 25000 | 200 | 3000 | OMNI | 5000K | 80 | 6.3 | 3.3 | E26 | 12 |
| * Not approved for enclosed luminaires | | | | | | | | | | | | | | |
| 18W LED A23 Non Dimmable | | | | | | | | | | | | | | |
| L125A23N25UNV27K | LED 125W A23 UNV 2700K | YES | - | 18 | 25000 | 125 | 2000 | OMNI | 2700K | 80 | 5.8 | 3.1 | E26 | 12 |
| L125A23N25UNV30K | LED 125W A23 UNV 3000K | NO | - | 18 | 25000 | 125 | 2000 | OMNI | 3000K | 80 | 5.8 | 3.1 | E26 | 12 |
| L125A23N25UNV40K | LED 125W A23 UNV 4000K | NO | - | 18 | 25000 | 125 | 2100 | OMNI | 4000K | 80 | 5.8 | 3.1 | E26 | 12 |
| L125A23N25UNV50K | LED 125W A23 UNV 5000K | YES | - | 18 | 25000 | 125 | 2200 | OMNI | 5000K | 80 | 5.8 | 3.1 | E26 | 12 |
| 14W LED A21 Non Dimmable | | | | | | | | | | | | | | |
| L100A21N25UNV27K | LED 14W A21 UNV 2700K | YES | - | 14 | 25000 | 100 | 1600 | OMNI | 2700K | 80 | 5.2 | 2.8 | E26 | 12 |
| L100A21N25UNV30K | LED 14W A21 UNV 3000K | YES | - | 14 | 25000 | 100 | 1625 | OMNI | 3000K | 80 | 5.2 | 2.8 | E26 | 12 |
| L100A21N25UNV40K | LED 14W A21 UNV 4000K | YES | - | 14 | 25000 | 100 | 1650 | OMNI | 4000K | 80 | 5.2 | 2.8 | E26 | 12 |
| L100A21N25UNV50K | LED 14W A21 UNV 5000K | YES | - | 14 | 25000 | 100 | 1650 | OMNI | 5000K | 80 | 5.2 | 2.8 | E26 | 12 |
| 7.5W LED A19 Non Dimmable | | | | | | | | | | | | | | |
| L60A19N25UNV27K | LED 60W A19 UNV 2700K | YES | - | 7.5 | 25000 | 60 | 800 | OMNI | 2700K | 80 | 4.1 | 2.4 | E26 | 12 |
| L60A19N25UNV30K | LED 60W A19 UNV 3000K | YES | - | 7.5 | 25000 | 60 | 800 | OMNI | 3000K | 80 | 4.1 | 2.4 | E26 | 12 |
| L60A19N25UNV40K | LED 60W A19 UNV 4000K | YES | - | 7.5 | 25000 | 60 | 850 | OMNI | 4000K | 80 | 4.1 | 2.4 | E26 | 12 |
| L60A19N25UNV50K | LED 60W A19 UNV 5000K | YES | - | 7.5 | 25000 | 60 | 875 | OMNI | 5000K | 80 | 4.1 | 2.4 | E26 | 12 |
| 9.5W LED BR30 Non Dimmable | | | | | | | | | | | | | | |
| L65BR30N25UNV27K | LED 65W BR30 UNV 2700K | YES | - | 9.5 | 25000 | 65 | 900 | 110° | 2700K | 80 | 5.2 | 3.8 | E26 | 12 |
| L65BR30N25UNV30K | LED 65W BR30 UNV 3000K | YES | - | 9.5 | 25000 | 65 | 900 | 110° | 3000K | 80 | 5.2 | 3.8 | E26 | 12 |
| L65BR30N25UNV40K | LED 65W BR30 UNV 4000K | YES | - | 9.5 | 25000 | 65 | 925 | 110° | 4000K | 80 | 5.2 | 3.8 | E26 | 12 |
| L65BR30N25UNV50K | LED 65W BR30 UNV 5000K | YES | - | 9.5 | 25000 | 65 | 1000 | 110° | 5000K | 80 | 5.2 | 3.8 | E26 | 12 |
| 13W LED BR30 Non Dimmable | | | | | | | | | | | | | | |
| L100BR30N25UNV27K | LED 100W BR30 UNV 2700K | YES | - | 13 | 25000 | 100 | 1400 | 110° | 2700K | 80 | 5.3 | 3.6 | E26 | 12 |
| L100BR30N25UNV30K | LED 100W BR30 UNV 3000K | YES | - | 13 | 25000 | 100 | 1400 | 110° | 3000K | 80 | 5.3 | 3.6 | E26 | 12 |
| L100BR30N25UNV40K | LED 100W BR30 UNV 4000K | YES | - | 13 | 25000 | 100 | 1450 | 110° | 4000K | 80 | 5.3 | 3.6 | E26 | 12 |
| L100BR30N25UNV50K | LED 100W BR30 UNV 5000K | YES | - | 13 | 25000 | 100 | 1500 | 110° | 5000K | 80 | 5.3 | 3.6 | E26 | 12 |
| 12.5W LED PAR38 Non Dimmable | | | | | | | | | | | | | | |
| L100P38N25UNV27KFL | LED 90W P38 UNV 2700K Fld | YES | 2630 | 12.5 | 25000 | 90 | 1100 | 40° | 2700K | 80 | 5.2 | 4.8 | E26 | 12 |
| L100P38N25UNV30KFL | LED 90W P38 UNV 3000K Fld | YES | 2613 | 12.5 | 25000 | 90 | 1100 | 40° | 3000K | 80 | 5.2 | 4.8 | E26 | 12 |
| L100P38N25UNV40KFL | LED 90W P38 UNV 4000K Fld | YES | 2532 | 12.5 | 25000 | 90 | 1150 | 40° | 4000K | 80 | 5.2 | 4.8 | E26 | 12 |
| L100P38N25UNV50KFL | LED 90W P38 UNV 5000K Fld | YES | 2641 | 12.5 | 25000 | 90 | 1200 | 40° | 5000K | 80 | 5.2 | 4.8 | E26 | 12 |
| L100P38N25UNV27KNFL | LED 90W P38 UNV 2700K Nar Fld | YES | 6245 | 12.5 | 25000 | 90 | 1100 | 25° | 2700K | 80 | 5.2 | 4.8 | E26 | 12 |
| L100P38N25UNV30KNFL | LED 90W P38 UNV 3000K Nar Fld | YES | 6334 | 12.5 | 25000 | 90 | 1100 | 25° | 3000K | 80 | 5.2 | 4.8 | E26 | 12 |
| L100P38N25UNV40KNFL | LED 90W P38 UNV 4000K Nar Fld | YES | 6412 | 12.5 | 25000 | 90 | 1150 | 25° | 4000K | 80 | 5.2 | 4.8 | E26 | 12 |
| L100P38N25UNV50KNFL | LED 90W P38 UNV 5000K Nar Fld | YES | 6572 | 12.5 | 25000 | 90 | 1200 | 25° | 5000K | 80 | 5.2 | 4.8 | E26 | 12 |

TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 20 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:

Date:

Model:

Project:

Rep:

Catalog Number:

Type:

Notes:



For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit tcpi.com

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516