



# LED COB PAR Lamps

## Product Specifications



TCP's award winning PAR lamps combine traditional beauty with top-notch technology. With the wide variety of options available, you can be sure to find the PAR lamp to meet your needs.

### Reasons to choose the LED COB PAR Lamps from TCP

- Provides designer grade light quality with same look as halogen replacements
- Perfect for sensitive display lighting such as galleries
- Enhances colors of focal point while maintaining uniformity throughout the lighting installation
- Track or downlight installations are not strained by excess weight
- Suitable for wet locations—when exposed to water, use only with device base up
- Seamlessly blends into lighting applications

### Ideal Applications

- Retail
- Display lights
- Track lighting
- Outdoor settings
- Galleries

### Specifications

Voltage ..... 120V  
 Input Line Frequency..... 50/60HZ  
 Lamp Life (Rated) ..... 25,000 hours  
 Minimum Starting Temp ..... -7.6°F/-22°C  
 Maximum Operating Temp..... 113°F/ 45°C

CRI ..... ≥ 80  
 Beam Angle ..... 15°, 25°, 40°, 60°  
 Base ..... E26  
 Warranty ..... 5 Years  
 Suitable for use in totally enclosed fixtures



## Specifications



ITEM #	DESCRIPTION	WATTS	REPLACEMENT WATTS	LUMENS	LPW	COLOR	CRI	MOL (inches)	DIA (inches)	MEASURED CBCP	BEAM ANGLE
<b>7W P20 Lamps – Dimmable • 25,000 Hours – PHASING OUT for L7P20D25 series, See new PAR20 spec sheet.</b>											
LED8P20D24KFL	LED 7W P20 DIM 24KFL	7	50	550	78.6	2400K	80	3.5"	2.5"	—	40°
LED8P20D24KNFL	LED 7W P20 DIM 24KNFL	7	50	550	78.6	2400K	80	3.5"	2.5"	—	25°
LED8P20D27KFL	LED 7W P20 DIM 27KFL	7	50	600	85.7	2700K	80	3.5"	2.5"	1208	40°
LED8P20D27KFLB	LED 7W P20 DIM 27KFL BLACK	7	50	600	85.7	2700K	80	3.5"	2.5"	1208	40°
LED8P20D27KNFL	LED 7W P20 DIM 27KNFL	7	50	600	85.7	2700K	80	3.5"	2.5"	2030	25°
LED8P20D27KNFLB	LED 7W P20 DIM 27KNFL BLACK	7	50	600	85.7	2700K	80	3.5"	2.5"	2030	25°
LED8P20D27KSP	LED 7W P20 DIM 27KSP	7	50	600	85.7	2700K	80	3.5"	2.5"	4898	15°
LED8P20D30KFL	LED 7W P20 DIM 30KFL	7	50	625	89.3	3000K	80	3.5"	2.5"	1187	40°
LED8P20D30KFLB	LED 7W P20 DIM 30KFL BLACK	7	50	625	89.3	3000K	80	3.5"	2.5"	1187	40°
LED8P20D30KNFL	LED 7W P20 DIM 30KNFL	7	50	625	89.3	3000K	80	3.5"	2.5"	2050	25°
LED8P20D30KNFLB	LED 7W P20 DIM 30KNFL BLACK	7	50	625	89.3	3000K	80	3.5"	2.5"	2050	25°
LED8P20D30KSP	LED 7W P20 DIM 30KSP	7	50	625	89.3	3000K	80	3.5"	2.5"	5391	15°
LED8P20D35KFL	LED 7W P20 DIM 35KFL	7	50	675	96.4	3500K	80	3.5"	2.5"	1722	40°
LED8P20D35KNFL	LED 7W P20 DIM 35KNFL	7	50	675	96.4	3500K	80	3.5"	2.5"	4807	25°
LED8P20D41KFL	LED 7W P20 DIM 41KFL	7	50	675	96.4	4100K	80	3.5"	2.5"	1383	40°
LED8P20D41KFLB	LED 7W P20 DIM 41KFL BLACK	7	50	675	96.4	4100K	80	3.5"	2.5"	1383	40°
LED8P20D41KNFL	LED 7W P20 DIM 41KNFL	7	50	675	96.4	4100K	80	3.5"	2.5"	2174	25°
LED8P20D41KNFLB	LED 7W P20 DIM 41KNFL BLACK	7	50	675	96.4	4100K	80	3.5"	2.5"	2174	25°
LED8P20D41KSP	LED 7W P20 DIM 41KSP	7	50	675	96.4	4100K	80	3.5"	2.5"	5411	15°
LED8P20D50KFL	LED 7W P20 DIM 50KFL	7	50	700	100	5000K	80	3.5"	2.5"	1330	40°
LED8P20D50KFLB	LED 7W P20 DIM 50KFL BLACK	7	50	700	100	5000K	80	3.5"	2.5"	1330	40°
LED8P20D50KNFL	LED 7W P20 DIM 50KNFL	7	50	700	100	5000K	80	3.5"	2.5"	2172	25°
LED8P20D50KSP	LED 7W P20 DIM 50KSP	7	50	700	100	5000K	80	3.5"	2.5"	5599	15°
<b>10W P30 Short Neck Lamps – Dimmable • 25,000 Hours</b>											
LED12P30SD24KFL	LED 10W P30SN DIM 24KFL	10	75	800	90.0	2400K	80	3.6"	3.8"	1619	40°
LED12P30SD24KNFL	LED 10W P30SN DIM 24KNFL	10	75	800	90.0	2400K	80	3.6"	3.8"	—	25°
LED12P30SD24KSP	LED 10W P30SN DIM 24KSP	10	75	800	85.0	2400K	80	3.6"	3.8"	—	15°
LED12P30SD27KFL	LED 10W P30SN DIM 27KFL	10	75	850	85.0	2700K	80	3.6"	3.8"	1817	40°
LED12P30SD27KFLB	LED 10W P30SN DIM 27KFL BLACK	10	75	850	85.0	2700K	80	3.6"	3.8"	1817	40°
LED12P30SD27KNFL	LED 10W P30SN DIM 27KNFL	10	75	850	85.0	2700K	80	3.6"	3.8"	4025	25°
LED12P30SD27KNFLB	LED 10W P30SN DIM 27KNFL BLACK	10	75	850	85.0	2700K	80	3.6"	3.8"	4025	25°
LED12P30SD27KSP	LED 10W P30SN DIM 27KSP	10	75	850	85.0	2700K	80	3.6"	3.8"	8042	15°
LED12P30SD30KFL	LED 10W P30SN DIM 30KFL	10	75	850	85.0	3000K	80	3.6"	3.8"	1858	40°
LED12P30SD30KFLB	LED 10W P30SN DIM 30KFL BLACK	10	75	850	85.0	3000K	80	3.6"	3.8"	1858	40°

NOTE: All items come in shipping cartons of 12.



# LED COB PAR Lamps

ITEM #	DESCRIPTION	WATTS	REPLACEMENT WATTS	LUMENS	LPW	COLOR	CRI	MOL (inches)	DIA (inches)	MEASURED CBCP	BEAM ANGLE
<b>10W P30 Short Neck Lamps – Dimmable • 25,000 Hours - Continued</b>											
LED12P30SD30KNFL	LED 10W P30SN DIM 30KNFL	10	75	850	85.0	3000K	80	3.6"	3.8"	4968	25°
LED12P30SD30KNFLB	LED 10W P30SN DIM 30KNFL BLACK	10	75	850	85.0	3000K	80	3.6"	3.8"	4968	25°
LED12P30SD30KSP	LED 10W P30SN DIM 30KSP	10	75	850	85.0	3000K	80	3.6"	3.8"	8380	15°
LED12P30SD30KSPB	LED 10W P30SN DIM 30KSP BLACK	10	75	850	85.0	3000K	80	3.6"	3.8"	8380	15°
LED12P30SD35KFL	LED 10W P30SN DIM 35KFL	10	75	850	85.0	3500K	80	3.6"	3.8"	2232	40°
LED12P30SD35KFLB	LED 10W P30SN DIM 35KFL BLACK	10	75	850	85.0	3500K	80	3.6"	3.8"	2232	40°
LED12P30SD35KNFL	LED 10W P30SN DIM 35KNFL	10	75	850	85.0	3500K	80	3.6"	3.8"	4402	25°
LED12P30SD35KNFLB	LED 10W P30SN DIM 35KNFL BLACK	10	75	850	85.0	3500K	80	3.6"	3.8"	4402	25°
LED12P30SD35KSP	LED 10W P30SN DIM 35KSP	10	75	850	85.0	3500K	80	3.6"	3.8"	—	15°
LED12P30SD41KFL	LED 10W P30SN DIM 41KFL	10	75	850	85.0	4100K	80	3.6"	3.8"	2247	40°
LED12P30SD41KFLB	LED 10W P30SN DIM 41KFL BLACK	10	75	850	85.0	4100K	80	3.6"	3.8"	2247	40°
LED12P30SD41KNFL	LED 10W P30SN DIM 41KNFL	10	75	850	85.0	4100K	80	3.6"	3.8"	4895	25°
LED12P30SD41KSP	LED 10W P30SN DIM 41KSP	10	75	850	85.0	4100K	80	3.6"	3.8"	8710	15°
LED12P30SD50KFL	LED 10W P30SN DIM 50KFL	10	75	850	85.0	5000K	80	3.6"	3.8"	2454	40°
LED12P30SD50KNFL	LED 10W P30SN DIM 50KNFL	10	75	850	85.0	5000K	80	3.6"	3.8"	5260	25°
LED12P30SD50KSP	LED 10W P30SN DIM 50KSP	10	75	850	85.0	5000K	80	3.6"	3.8"	9292	15°
<b>10.5W P30 Lamps – Dimmable • 25,000 Hours</b>											
LED12P30D24KFL	LED 10.5W P30 DIM 24KFL	10.5	75	800	76.2	2400K	80	4.6"	3.8"	—	40°
LED12P30D24KNFL	LED 10.5W P30 DIM 24KNFL	10.5	75	800	76.2	2400K	80	4.6"	3.8"	—	25°
LED12P30D24KSP	LED 10.5W P30 DIM 24KSP	10.5	75	800	76.2	2400K	80	4.6"	3.8"	—	15°
LED12P30D27KFL	LED 10.5W P30 DIM 27KFL	10.5	75	850	81.0	2700K	80	4.6"	3.8"	2202	40°
LED12P30D27KFLB	LED 10.5W P30 DIM 27KFL BLACK	10.5	75	850	81.0	2700K	80	4.6"	3.8"	2202	40°
LED12P30D27KNFL	LED 10.5W P30 DIM 27KNFL	10.5	75	850	81.0	2700K	80	4.6"	3.8"	5031	25°
LED12P30D27KNFLB	LED 10.5W P30 DIM 27KNFL BLACK	10.5	75	850	81.0	2700K	80	4.6"	3.8"	5031	25°
LED12P30D27KSP	LED 10.5W P30 DIM 27KSP	10.5	75	850	81.0	2700K	80	4.6"	3.8"	9193	15°
LED12P30D27KSPB	LED 10.5W P30 DIM 27KSP BLACK	10.5	75	850	81.0	2700K	80	4.6"	3.8"	9193	15°
LED12P30D30KFL	LED 10.5W P30 DIM 30KFL	10.5	75	850	81.0	3000K	80	4.6"	3.8"	2389	40°
LED12P30D30KFLB	LED 10.5W P30 DIM 30KFL BLACK	10.5	75	850	81.0	3000K	80	4.6"	3.8"	2389	40°
LED12P30D30KNFL	LED 10.5W P30 DIM 30KNFL	10.5	75	850	81.0	3000K	80	4.6"	3.8"	5528	25°
LED12P30D30KNFLB	LED 10.5W P30 DIM 30KNFL BLACK	10.5	75	850	81.0	3000K	80	4.6"	3.8"	5528	25°
LED12P30D30KSP	LED 10.5W P30 DIM 30KSP	10.5	75	850	81.0	3000K	80	4.6"	3.8"	9006	15°
LED12P30D30KSPB	LED 10.5W P30 DIM 30KSP BLACK	10.5	75	850	81.0	3000K	80	4.6"	3.8"	9006	15°
LED12P30D35KFL	LED 10.5W P30 DIM 35KFL	10.5	75	850	81.0	3500K	80	4.6"	3.8"	2362	40°
LED12P30D35KNFL	LED 10.5W P30 DIM 35KNFL	10.5	75	850	81.0	3500K	80	4.6"	3.8"	5029	25°
LED12P30D35KSP	LED 10.5W P30 DIM 35KSP	10.5	75	850	81.0	3500K	80	4.6"	3.8"	9735	15°
LED12P30D41KFL	LED 10.5W P30 DIM 41KFL	10.5	75	850	81.0	4100K	80	4.6"	3.8"	2561	40°
LED12P30D41KFLB	LED 10.5W P30 DIM 41KFL BLACK	10.5	75	850	81.0	4100K	80	4.6"	3.8"	2561	40°
LED12P30D41KNFL	LED 10.5W P30 DIM 41KNFL	10.5	75	850	81.0	4100K	80	4.6"	3.8"	5781	25°
LED12P30D41KNFLB	LED 10.5W P30 DIM 41KNFL BLACK	10.5	75	850	81.0	4100K	80	4.6"	3.8"	5781	25°
LED12P30D41KSP	LED 10.5W P30 DIM 41KSP	10.5	75	850	81.0	4100K	80	4.6"	3.8"	9491	15°
LED12P30D41KSPB	LED 10.5W P30 DIM 41KSP BLACK	10.5	75	850	81.0	4100K	80	4.6"	3.8"	9491	15°
LED12P30D50KFL	LED 10.5W P30 DIM 50KFL	10.5	75	850	81.0	5000K	80	4.6"	3.8"	2437	40°
LED12P30D50KFLB	LED 10.5W P30 DIM 50KFL BLACK	10.5	75	850	81.0	5000K	80	4.6"	3.8"	2437	40°
LED12P30D50KNFL	LED 10.5W P30 DIM 50KNFL	10.5	75	850	81.0	5000K	80	4.6"	3.8"	5575	25°
LED12P30D50KSP	LED 10.5W P30 DIM 50KSP	10.5	75	850	81.0	5000K	80	4.6"	3.8"	9647	15°

NOTE: All items come in shipping cartons of 12.





# LED COB PAR Lamps

ITEM #	DESCRIPTION	WATTS	REPLACEMENT WATTS	LUMENS	LPW	COLOR	CRI	MOL (inches)	DIA (inches)	MEASURED CBCP	BEAM ANGLE
<b>13.5W P30 Lamps – Dimmable • 25,000 Hours</b>											
LED14P30D24KFL	LED 13.5W P30 DIM 24KFL	13.5	75	1000	74.1	2400K	80	4.6"	3.8"	—	40°
LED14P30D24KNFL	LED 13.5W P30 DIM 24KNFL	13.5	75	1000	74.1	2400K	80	4.6"	3.8"	—	25°
LED14P30D24KNFLB	LED 13.5W P30 DIM 24KNFL BLACK	13.5	75	1000	74.1	2400K	80	4.6"	3.8"	—	25°
LED14P30D24KSP	LED 13.5W P30 DIM 24KSP	13.5	75	1000	74.1	2400K	80	4.6"	3.8"	—	15°
LED14P30D27KFL	LED 13.5W P30 DIM 27KFL	13.5	75	1050	77.8	2700K	80	4.6"	3.8"	2693	40°
LED14P30D27KFLB	LED 13.5W P30 DIM 27KFL BLACK	13.5	75	1050	77.8	2700K	80	4.6"	3.8"	2693	40°
LED14P30D27KNFL	LED 13.5W P30 DIM 27KNFL	13.5	75	1050	77.8	2700K	80	4.6"	3.8"	5808	25°
LED14P30D27KNFLB	LED 13.5W P30 DIM 27KNFL BLACK	13.5	75	1050	77.8	2700K	80	4.6"	3.8"	5808	25°
LED14P30D27KSP	LED 13.5W P30 DIM 27KSP	13.5	75	1050	77.8	2700K	80	4.6"	3.8"	10563	15°
LED14P30D27KSPB	LED 13.5W P30 DIM 27KSP BLACK	13.5	75	1050	77.8	2700K	80	4.6"	3.8"	10563	15°
LED14P30D30KFL	LED 13.5W P30 DIM 30KFL	13.5	75	1050	77.8	3000K	80	4.6"	3.8"	2849	40°
LED14P30D30KFLB	LED 13.5W P30 DIM 30KFLB	13.5	75	1050	77.8	3000K	80	4.6"	3.8"	2849	40°
LED14P30D30KNFL	LED 13.5W P30 DIM 30KNFL	13.5	75	1050	77.8	3000K	80	4.6"	3.8"	6392	25°
LED14P30D30KNFLB	LED 13.5W P30 DIM 30KNFL BLACK	13.5	75	1050	77.8	3000K	80	4.6"	3.8"	6392	25°
LED14P30D30KSP	LED 13.5W P30 DIM 30KSP	13.5	75	1050	77.8	3000K	80	4.6"	3.8"	11181	15°
LED14P30D30KSPB	LED 13.5W P30 DIM 30KSP BLACK	13.5	75	1050	77.8	3000K	80	4.6"	3.8"	11181	15°
LED14P30D35KFL	LED 13.5W P30 DIM 35KFL	13.5	75	1050	77.8	3500K	80	4.6"	3.8"	—	40°
LED14P30D35KFLB	LED 13.5W P30 DIM 35KFL BLACK	13.5	75	1050	77.8	3500K	80	4.6"	3.8"	—	40°
LED14P30D35KNFL	LED 13.5W P30 DIM 35KNFL	13.5	75	1050	77.8	3500K	80	4.6"	3.8"	—	25°
LED14P30D35KSP	LED 13.5W P30 DIM 35KSP	13.5	75	1050	77.8	3500K	80	4.6"	3.8"	—	15°
LED14P30D41KFL	LED 13.5W P30 DIM 41KFL	13.5	75	1050	77.8	4100K	80	4.6"	3.8"	2661	40°
LED14P30D41KFLB	LED 13.5W P30 DIM 41KFL BLACK	13.5	75	1050	77.8	4100K	80	4.6"	3.8"	2661	40°
LED14P30D41KNFL	LED 13.5W P30 DIM 41KNFL	13.5	75	1050	77.8	4100K	80	4.6"	3.8"	5781	25°
LED14P30D41KNFLB	LED 13.5W P30 DIM 41KNFL BLACK	13.5	75	1050	77.8	4100K	80	4.6"	3.8"	5781	25°
LED14P30D41KSP	LED 13.5W P30 DIM 41KSP	13.5	75	1050	77.8	4100K	80	4.6"	3.8"	12465	15°
LED14P30D41KSPB	LED 13.5W P30 DIM 41KSP BLACK	13.5	75	1050	77.8	4100K	80	4.6"	3.8"	12465	15°
LED14P30D50KFL	LED 13.5W P30 DIM 50KFL	13.5	75	1050	77.8	5000K	80	4.6"	3.8"	2837	40°
LED14P30D50KFLB	LED 13.5W P30 DIM 50KFL BLACK	13.5	75	1050	77.8	5000K	80	4.6"	3.8"	2837	40°
LED14P30D50KNFL	LED 13.5W P30 DIM 50KNFL	13.5	75	1050	77.8	5000K	80	4.6"	3.8"	5875	25°
LED14P30D50KSP	LED 13.5W P30 DIM 50KSP	13.5	75	1050	77.8	5000K	80	4.6"	3.8"	12073	15°
<b>13.5W P38 Lamps – Dimmable • 25,000 Hours</b>											
LED14P38D24KFL	LED 13.5W P38 DIM 24KFL	13.5	90	1000	74.1	2400K	80	5.3"	4.8"	—	40°
LED14P38D24KNFL	LED 13.5W P38 DIM 24KNFL	13.5	90	1000	74.1	2400K	80	5.3"	4.8"	—	25°
LED14P38D24KSP	LED 13.5W P38 DIM 24KSP	13.5	90	1000	74.1	2400K	80	5.3"	4.8"	—	15°
LED14P38D27KFL	LED 13.5W P38 DIM 27KFL	13.5	90	1050	77.8	2700K	80	5.3"	4.8"	2480	40°
LED14P38D27KNFL	LED 13.5W P38 DIM 27KNFL	13.5	90	1050	77.8	2700K	80	5.3"	4.8"	7649	25°
LED14P38D27KNFLB	LED 13.5W P38 DIM 27KNFL BLACK	13.5	90	1050	77.8	2700K	80	5.3"	4.8"	7649	25°
LED14P38D27KSP	LED 13.5W P38 DIM 27KSP	13.5	90	1050	77.8	2700K	80	5.3"	4.8"	12073	15°
LED14P38D27KSPB	LED 13.5W P38 DIM 27KSP BLACK	13.5	90	1050	77.8	2700K	80	5.3"	4.8"	12073	15°
LED14P38D30KFL	LED 13.5W P38 DIM 30KFL	13.5	90	1050	77.8	3000K	80	5.3"	4.8"	2498	40°
LED14P38D30KNFL	LED 13.5W P38 DIM 30KNFL	13.5	90	1050	77.8	3000K	80	5.3"	4.8"	7606	25°
LED14P38D30KSP	LED 13.5W P38 DIM 30KSP	13.5	90	1050	77.8	3000K	80	5.3"	4.8"	11845	15°
LED14P38D30KWFL	LED 13.5W P38 DIM 30KWFL	13.5	90	1050	77.8	3000K	80	5.3"	4.8"	—	60°
LED14P38D35KFL	LED 13.5W P38 DIM 35KFL	13.5	90	1050	77.8	3500K	80	5.3"	4.8"	2736	40°
LED14P38D35KFLB	LED 13.5W P38 DIM 35KFL BLACK	13.5	90	1050	77.8	3500K	80	5.3"	4.8"	2736	40°
LED14P38D35KNFL	LED 13.5W P38 DIM 35KNFL	13.5	90	1050	77.8	3500K	80	5.3"	4.8"	—	25°
LED14P38D35KSP	LED 13.5W P38 DIM 35KSP	13.5	90	1050	77.8	3500K	80	5.3"	4.8"	12856	15°

NOTE: All items come in shipping cartons of 12.





# LED COB PAR Lamps

ITEM #	DESCRIPTION	WATTS	REPLACEMENT WATTS	LUMENS	LPW	COLOR	CRI	MOL (inches)	DIA (inches)	MEASURED CBCP	BEAM ANGLE
<b>13.5W P38 Lamps – Dimmable • 25,000 Hours - Continued</b>											
LED14P38D41KFL	LED 13.5W P38 DIM 41KFL	13.5	90	1050	77.8	4100K	80	5.3"	4.8"	2678	40°
LED14P38D41KFLB	LED 13.5W P38 DIM 41KFL BLACK	13.5	90	1050	77.8	4100K	80	5.3"	4.8"	2678	40°
LED14P38D41KNFL	LED 13.5W P38 DIM 41KNFL	13.5	90	1050	77.8	4100K	80	5.3"	4.8"	8310	25°
LED14P38D41KSP	LED 13.5W P38 DIM 41KSP	13.5	90	1050	77.8	4100K	80	5.3"	4.8"	13535	15°
LED14P38D41KSPB	LED 13.5W P38 DIM 41KSP BLACK	13.5	90	1050	77.8	4100K	80	5.3"	4.8"	13535	15°
LED14P38D50KFL	LED 13.5W P38 DIM 50KFL	13.5	90	1050	77.8	5000K	80	5.3"	4.8"	2647	40°
LED14P38D50KFLB	LED 13.5W P38 DIM 50KFL BLACK	13.5	90	1050	77.8	5000K	80	5.3"	4.8"	2647	40°
LED14P38D50KNFL	LED 13.5W P38 DIM 50KNFL	13.5	90	1050	77.8	5000K	80	5.3"	4.8"	8071	25°
LED14P38D50KSP	LED 13.5W P38 DIM 50KSP	13.5	90	1050	77.8	5000K	80	5.3"	4.8"	12418	15°
<b>15W P38 Lamps – Dimmable • 25,000 Hours</b>											
LED17P38D24KFL	LED 15W P38 DIM 24KFL	15	120	1050	70.0	2400K	80	5.3"	4.8"	–	40°
LED17P38D24KNFL	LED 15W P38 DIM 24KNFL	15	120	1050	70.0	2400K	80	5.3"	4.8"	–	25°
LED17P38D24KSP	LED 15W P38 DIM 24KSP	15	120	1050	70.0	2400K	80	5.3"	4.8"	–	15°
LED17P38D27KFL	LED 15W P38 DIM 27KFL	15	120	1200	80.0	2700K	80	5.3"	4.8"	2757	40°
LED17P38D27KFLB	LED 15W P38 DIM 27KFL BLACK	15	120	1200	80.0	2700K	80	5.3"	4.8"	2757	40°
LED17P38D27KNFL	LED 15W P38 DIM 27KNFL	15	120	1200	80.0	2700K	80	5.3"	4.8"	8857	25°
LED17P38D27KSP	LED 15W P38 DIM 27KSP	15	120	1200	80.0	2700K	80	5.3"	4.8"	16239	15°
LED17P38D30KFL	LED 15W P38 DIM 30KFL	15	120	1200	80.0	3000K	80	5.3"	4.8"	3106	40°
LED17P38D30KFLB	LED 15W P38 DIM 30KFL BLACK	15	120	1200	80.0	3000K	80	5.3"	4.8"	3106	40°
LED17P38D30KNFL	LED 15W P38 DIM 30KNFL	15	120	1200	80.0	3000K	80	5.3"	4.8"	9274	25°
LED17P38D30KNFLB	LED 15W P38 DIM 30KNFL BLACK	15	120	1200	80.0	3000K	80	5.3"	4.8"	9274	25°
LED17P38D30KSP	LED 15W P38 DIM 30KSP	15	120	1200	80.0	3000K	80	5.3"	4.8"	18492	15°
LED17P38D30KSPB	LED 15W P38 DIM 30KSP BLACK	15	120	1200	80.0	3000K	80	5.3"	4.8"	18492	15°
LED17P38D30KWFLB	LED 15W P38 DIM 30KWFL BLACK	15	120	1200	80.0	3000K	80	5.3"	4.8"	–	60°
LED17P38D35KFL	LED 15W P38 DIM 35KFL	15	120	1200	80.0	3500K	80	5.3"	4.8"	2994	40°
LED17P38D35KFLB	LED 15W P38 DIM 35KFL BLACK	15	120	1200	80.0	3500K	80	5.3"	4.8"	2994	40°
LED17P38D35KNFL	LED 15W P38 DIM 35KNFL	15	120	1200	80.0	3500K	80	5.3"	4.8"	9405	25°
LED17P38D35KNFLB	LED 15W P38 DIM 35KNFL BLACK	15	120	1200	80.0	3500K	80	5.3"	4.8"	9405	25°
LED17P38D35KSP	LED 15W P38 DIM 35KSP	15	120	1200	80.0	3500K	80	5.3"	4.8"	18094	15°
LED17P38D41KFL	LED 15W P38 DIM 41KFL	15	120	1200	80.0	4100K	80	5.3"	4.8"	2870	40°
LED17P38D41KFLB	LED 15W P38 DIM 41KFL BLACK	15	120	1200	80.0	4100K	80	5.3"	4.8"	2870	40°
LED17P38D41KNFL	LED 15W P38 DIM 41KNFL	15	120	1200	80.0	4100K	80	5.3"	4.8"	9288	25°
LED17P38D41KNFLB	LED 15W P38 DIM 41KNFLB	15	120	1200	80.0	4100K	80	5.3"	4.8"	9288	25°
LED17P38D41KSP	LED 15W P38 DIM 41KSP	15	120	1200	80.0	4100K	80	5.3"	4.8"	18408	15°
LED17P38D41KSPB	LED 15W P38 DIM 41KSP BLACK	15	120	1200	80.0	4100K	80	5.3"	4.8"	18408	15°
LED17P38D50KFL	LED 15W P38 DIM 50KFL	15	120	1200	80.0	5000K	80	5.3"	4.8"	2713	40°
LED17P38D50KFLB	LED 15W P38 DIM 50KFL BLACK	15	120	1200	80.0	5000K	80	5.3"	4.8"	2713	40°
LED17P38D50KNFL	LED 15W P38 DIM 50KNFL	15	120	1200	80.0	5000K	80	5.3"	4.8"	9387	25°
LED17P38D50KSP	LED 15W P38 DIM 50KSP	15	120	1200	80.0	5000K	80	5.3"	4.8"	19721	15°

NOTE: All items come in shipping cartons of 12.





# LED COB PAR Lamps

ITEM #	DESCRIPTION	WATTS	REPLACEMENT WATTS	LUMENS	LPW	COLOR	CRI	MOL (inches)	DIA (inches)	MEASURED CBCP	BEAM ANGLE
<b>18.5W P38 High Output Lamps – Dimmable • 25,000 Hours</b>											
LED17HOP38D27KFL	LED 18.5W HOP38 DIM 27KFL	18.5	150	1800	97.3	2700K	80	5.3"	4.8"	4346	40°
LED17HOP38D27KNFL	LED 18.5W HOP38 DIM 27KNFL	18.5	150	1800	97.3	2700K	80	5.3"	4.8"	9299	25°
LED17HOP38D27KSP	LED 18.5W HOP38 DIM 27KSP	18.5	150	1800	97.3	2700K	80	5.3"	4.8"	21535	15°
LED17HOP38D27KSPB	LED 18.5W HOP38 DIM 27KSP BLACK	18.5	150	1800	97.3	2700K	80	5.3"	4.8"	21535	15°
LED17HOP38D30KFL	LED 18.5W HOP38 DIM 30KFL	18.5	150	1825	98.6	3000K	80	5.3"	4.8"	4365	40°
LED17HOP38D30KFLB	LED 18.5W HOP38 DIM 30KFL BLACK	18.5	150	1825	98.6	3000K	80	5.3"	4.8"	4365	40°
LED17HOP38D30KNFL	LED 18.5W HOP38 DIM 30KNFL	18.5	150	1825	98.6	3000K	80	5.3"	4.8"	12782	25°
LED17HOP38D30KNFLB	LED 18.5W HOP38 DIM 30KNFL BLACK	18.5	150	1825	98.6	3000K	80	5.3"	4.8"	12782	25°
LED17HOP38D30KSP	LED 18.5W HOP38 DIM 30KSP	18.5	150	1825	98.6	3000K	80	5.3"	4.8"	23699	15°
LED17HOP38D30KSPB	LED 18.5W HOP38 DIM 30KSP BLACK	18.5	150	1825	98.6	3000K	80	5.3"	4.8"	23699	15°
LED17HOP38D35KFL	LED 18.5W HOP38 DIM 35KFL	18.5	150	1850	100.0	3500K	80	5.3"	4.8"	3481	40°
LED17HOP38D35KFLB	LED 18.5W HOP38 DIM 35KFL BLACK	18.5	150	1850	100.0	3500K	80	5.3"	4.8"	3481	40°
LED17HOP38D35KNFL	LED 18.5W HOP38 DIM 35KNFL	18.5	150	1850	100.0	3500K	80	5.3"	4.8"	11664	25°
LED17HOP38D35KSP	LED 18.5W HOP38 DIM 35KSP	18.5	150	1850	100.0	3500K	80	5.3"	4.8"	23145	15°
LED17HOP38D35KWFL	LED 18.5W HOP38 DIM 35KWFL	18.5	150	1850	100.0	3500K	80	5.3"	4.8"	—	60°
LED17HOP38D41KFL	LED 18.5W HOP38 DIM 41KFL	18.5	150	1900	102.7	4100K	80	5.3"	4.8"	4604	40°
LED17HOP38D41KNFL	LED 18.5W HOP38 DIM 41KNFL	18.5	150	1900	102.7	4100K	80	5.3"	4.8"	11664	25°
LED17HOP38D41KSP	LED 18.5W HOP38 DIM 41KSP	18.5	150	1900	102.7	4100K	80	5.3"	4.8"	22458	15°
LED17HOP38D50KFL	LED 18.5W HOP38 DIM 50KFL	18.5	150	2000	108.1	5000K	80	5.3"	4.8"	4446	40°
LED17HOP38D50KNFL	LED 18.5W HOP38 DIM 50KNFL	18.5	150	2000	108.1	5000K	80	5.3"	4.8"	12467	25°
LED17HOP38D50KSP	LED 18.5W HOP38 DIM 50KSP	18.5	150	2000	108.1	5000K	80	5.3"	4.8"	21535	15°

NOTE: All items come in shipping cartons of 12.



# TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 20 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:

Date:

Model:

Project:

Rep:

Catalog Number:

Type:

Notes:



For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit [tcpi.com](http://tcpi.com)

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516