



LED Dimmable Globe Lamps



TCP's LED dimmable globe lamps provide the lighting you need at a cost you will love. Advanced factory techniques and rigorous testing ensure each lamp is perfect from day one.

Reasons to choose the LED Dimmable Globe Lamps from TCP

- Smooth, uniform dimming from 100% to 10%
- Energy efficient: Up to 80% less energy than standard incandescent
- Long life: 25,000 hours
- Very durable: solid state lighting technology significantly reduces lighting service & maintenance due to robust lighting design

Ideal Applications

- Vanity strips
- Pendant lighting
- Decorative

Specifications:

Voltage	120VAC	Lamp Life (Rated)	25,000 hours
Input Power	5W/6W	Minimum Starting Temp	-20°C
Input Line Frequency.....	50/60HZ	Maximum Operating Temp.....	40°C



*Based on 12 hours use per day



LED Dimmable Globe Lamps

Specifications:



**G25
E26 Frost**



**G16
E12 Frost**



**G16
E12 Clear**



**G16
E26 Frost**



**G16
E26 Clear**

ITEM #	DESCRIPTION	ENERGY STAR	VOLTAGE	WATTAGE	WATTAGE EQUIVALENT	MOL (IN.)	DIA (IN.)	LUMENS	LPW	ENCLOSED LUMINAIRE	CCT	CRI
LED Globe G25 – Dimmable • 25,000 Hours												
LED5G25D27KF	Dimmable 4W Smooth G25 2700K, Frosted	★	120	4	40	4.4	3.1	350	87.5	Yes	2700K	80
LED5G25D30KF	Dimmable 4W Smooth G25 3000K, Frosted	★	120	4	40	4.4	3.1	350	87.5	Yes	3000K	80
L6G25D2527KF	Dimmable 6W Smooth G25 2700K, Frosted	★	120	6	60	4.4	3.1	525	87.5	Yes	2700K	80
L6G25D2530KF	Dimmable 6W Smooth G25 3000K, Frosted	★	120	6	60	4.4	3.1	525	87.5	Yes	3000K	80
LED Globe G16 – Dimmable • 25,000 Hours												
LED4E12G1627K	LED 4W G16 DIM 2700K E12	★	120	3.5	25	3.5	2.0	280	80	Yes	2700K	80
LED4E12G1627KF	LED 4W G16 DIM 2700K E12 FROST	★	120	3.5	25	3.5	2.0	280	80	Yes	2700K	80
LED4E26G1624KF	LED 4W G16 DIM 2400K E26 FROST		120	3.5	25	3.5	2.0	200	80	Yes	2400K	80
LED4E26G16S7K	LED 4W G16 DIM 2700K E26	★	120	3.5	25	3.5	2.0	280	80	Yes	2700K	80
LED4E26G1627KF	LED 4W G16 DIM 2700K E26 FROST	★	120	3.5	25	3.5	2.0	280	80	Yes	2700K	80
LED5E12G1627K	LED 5W G16 DIM 2700K E12		120	5	40	3.5	2.0	350	70	Yes	2700K	80
LED5E12G1627KF	LED 5W G16 DIM 2700K E12 FROST		120	5	40	3.5	2.0	350	70	Yes	2700K	80
LED5E26G1627K	LED 5W G16 DIM 2700K E26		120	5	40	3.5	2.0	350	70	Yes	2700K	80
LED5E26G1627KF	LED 5W G16 DIM 2700K E26 FROST		120	5	40	3.5	2.0	350	70	Yes	2700K	80

For the most up-to-date specs, please visit tcp.com

